



HDMI to VGA Converter

No.: 38291

Description

- Connects an HDMI equipped device to a VGA display
- Supports resolutions up to 1920x1200 including 1080p
- Direct signal conversion, without scaling
- Quick and simple plug and play installation
- 2 Year Warranty

This adapter converts signals from an HDMI equipped source into an analogue VGA signal. It supports resolutions up to 1080p and 1920x1200 for PC VGA displays. This allows the connection of modern HDMI capable devices, such as PC's, notebooks and ultrabooks, to an older VGA display or projector. The converter can also be used to add another display to extend the available desktop workspace. It is also ideally suited for travelling due to its compact, lightweight form factor and convenient plug & play installation.

Technical details

Connectors

- Connector A: HDMI Type A Male
- Connector B: VGA Female
- Housing Material: ABS
- Connector Plating: Nickel
- Pin Construction: Phosphor Bronze
- Pin Plating: Nickel
- Dimensions (approx.) WxDxH: 37x42x14.5mm (1.46x1.65x0.57in)

Cable Construction

- Length: 100mm (3.94in)
- Standard: HDMI 1.3
- Colour: Black
- Type: Round
- Jacket Diameter: 4.8mm (0.19in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 30AWG
- Shielding: Aluminium Braid + Mylar

Specifications

- Supported Bandwidth: 4.95 Gbps
- Maximum Resolution: 1920x1200@60Hz 12bit
- Nominal Attenuation:
 - 300kHz-825MHz <5dB
 - 825MHz-2.475GHz 5dB-12dB
 - 2.475GHz-4.125GHz 12dB-20dB
 - 4.125GHz-5.1GHz 20dB-25dB
- Minimum Bend Radius: -

- Operating Temperature: 0°C - 70°C (32°F - 158°F)
- Storage Temperature: -10°C - 80°C (14°F - 176°F)
- ATC Approved: -

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Purchasing Information

- No.: 38291
- EAN: 4002888382915

© LINDY 2018