

TAROX ParX T100ca G6v2

WITH INTEL® XEON® E-2224



SPECIFICATIONS

P/N	
Manufacturer	TAROX

CHASSIS

Chassis	SR20966
Formfactor	Tower
Width	198 mm
Heights	425 mm
Depth	465 mm
Colour	black
ODD Bay (5.25")	-
FDD Bay (3.5")	-
HDD Bay (2.5")	-
HDD Bay (3.5")	4

FRONT INTERFACES

USB 2.0	-
USB 3.2 Gen1	2
Line in	-
Line Out	-

PSU

Power	350 W
Efficiency	80+ Bronze

OPERATION SYSTEM

Operation System	-
Languages	-

MAINBOARD

Mainboard	P11C-M/4L
-----------	-----------

SYSTEM

CPU Socket	LGA1151
Chipset	Intel® C242
Audio Chipset	-
GPU	ASPEED AST2500 BMC
LAN Chipset	Quad LAN 1GbE with Intel® I210
PXE	ja
Wake on Lan (WoL)	ja
Trustes Plattform Module (TPM)	optional
Formfactor	mATX
Memory Support	DDR4 unbuffered ECC UDIMM
max. Memory	128 GB
max. Memory-Modules	32 GB

REAR INTERFACES

USB 3	4
USB 2.0	-
RS232	1
LPT	-
Displayport	-
HDMI	-
DVI	-
D-Sub	1
RJ-45	2
Management	IPMI 2.0, KVM with dedicated LAN

INTERNAL INTERFACES

PCI Express x16	1
PCI Express x8	1
PCI Express x4	-
USB 2.0	-
USB 3.0	2
RS232 (Header)	1
LPT (Header)	-
Trusted Plattform Module (TPM)	optional
S-ATA Controller	6

PROCESSOR(S)

Processor(s)	Intel Xeon E-2224
Base Clock	3,4 GHz
Turbo Clock	4,6 GHz
Cores	4
Cache	8 MB
Virtualization	VT-x,VT-d
TDP	71 W
Socket	LGA1151

MEMORY

Capacity	16 GB
Memory Type	UDIMM ECC
Memory-Modules (installed)	1

HDD / SSD

Capacity	480 GB 2,5" SATA
Solid State Disk (SSD)	yes

ODD

DVD+-R/RW	yes
-----------	-----

CERTIFICATES

Declaration of Conformity	yes
Production in Germany according to ISO9001	yes
WEEE-Reg.-Nr. DE 99267951	yes

SERVICE

Warranty	36 month
Service	optional