

Product datasheet

Specifications



APC NetShelter Rack PDU Advanced, Metered Outlet, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

APDU10350MO

Overview

Lead time

Main

Main Input Voltage	415 V 3 phases 400 V 3 phases
Product or component type	PDU
PDU type	Metered outlet
Main Output Voltage	240 V
Input Connection Type	IEC 60309 30 A 3P + N + PE
Number of rack unit	0U
Cable length	1.8 m
Communication port protocol	1000BASE-T 10/100BASE-T

Physical

Colour	Black
Height	178.0 cm
Width	5.6 cm
Depth	7.5 cm
Net weight	9.6 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Vertical

Input

[In] rated current	24 A
Permissible voltage	200...240 V 346...415 V
Input current limits	30 A
Load capacity	17300 VA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Network frequency	50/60 Hz
-------------------	----------

Output

Number of power socket outlets	24 C13/C15/C19/C21 24C13/C15
--------------------------------	---------------------------------

Conformance

Product certifications	UKCA TAA compliance
------------------------	------------------------

Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1
-----------	---

IP degree of protection	IP44
-------------------------	------

Environmental

Ambient air temperature for operation	-5...60 °C
---------------------------------------	------------

Relative humidity	5...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage altitude	0.00...15240.00 m
------------------	-------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	198 cm
------------------	--------

Package 1 Width	13.2 cm
-----------------	---------

Package 1 Length	26.2 cm
------------------	---------

Package 1 Weight	12.6 kg
------------------	---------

Offer Sustainability

REACH Regulation	REACH Declaration
------------------	-----------------------------------

REACH free of SVHC	Yes
--------------------	-----

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

RoHS exemption information	Yes
----------------------------	---------------------

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Recommended replacement(s)