

Rittal – The System.

Faster – better – everywhere.

Air duct for side air routing – SK 3301.392

Date : Dec 7, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Air duct for side air routing – SK 3301.392

created: 07.12.2020 on www.rittal.com/com-en



Product description

Description:	Air duct, passive, for cold air intake to 482.6 mm (19") IT equipment with side air inlet. Suitable for use in conjunction with all-round partitioning around the mounting level via air baffle plates and targeted management of the airflow through the air duct.
Benefits:	For superior air intake to the rear 482.6 mm (19") equipment with side air routing Integral membrane cover allows cable entry to the rear Depth-variable
Material:	Sheet steel
Surface finish:	Spray-finished
Colour:	RAL 9005
Assembly instruction:	Only suitable for fitting on the front 482.6 mm (19") installation level Can only be mounted in the area of the vertical 19" openings of the air baffle plate
Supply includes:	Air duct Adaptor for attaching to 482.6 mm (19") mounting angles Magnetic strip to cover the remaining vertical openings in the air baffle plate

Product features

Dimensions:	Height: 2 U
Installation options:	for TS IT 482.6 mm (19") mounting angles for TS IT 482.6 mm (19") mounting frames for 482.6 mm (19") mounting angles, standard
To fit:	TS IT

with width: 800 mm

eCl@ss 8.0/8.1:	22410601
Packs of:	1 pc(s).
Weight/pack:	1.8 kg
EAN:	4028177716612
Customs tariff number:	73269098
ETIM 7.0:	EC011217
ETIM 6.0:	EC001292
eCl@ss 8.0/8.1:	22410601
eCl@ss 6.0/6.1:	27189269
Product description:	SK Air duct, For side air flow, 2 U, Depth-variable 275 - 418 mm, Sheet steel, RAL 9005
Approvals	
Certificates:	EAC