



# Delock Adapter USB Type-C™ male > HDMI female (DP Alt Mode) 4K 60 Hz with PD function

## Description

This Delock adapter is suitable for the connection of a HDMI monitor to a computer with USB-C™ interface and Displayport alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface. The adapter has a USB Type-C™ Power Delivery port. This allows the laptop to be charged while the adapter is in use.



## Specification

- Connectors:
  - Input:
    - 1 x USB Type-C™ male
    - 1 x USB Type-C™ Power Delivery female (optional for power supply)
  - Output:
    - 1 x HDMI-A 19 pin female
- Chipset: VIA VL100 + Parade PS176
- Displayport 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 4096 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of audio and video signals
- Audio formats: 8-channel LPCM, compressed audio and HBR audio format up to 24 Bit audio sample size and 192 kHz sample rate
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- Charging power: max. 60 W, 20 V @ 3 A
- USB bus powered
- Plug & Play
- Housing material: aluminium
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: dark grey

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, Linux ex Kernel 4.3, Mac ex OS 10.12, Android ex 6.0
- PC or laptop with a free USB Type-C™ port and Displayport alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

## Package content

- USB-C™ to HDMI adapter

## Item no. 62988

EAN: 4043619629886

Country of origin: China

Package: Retail Box





Images





General	
Function:	Plug & Play
Specification:	Displayport 1.2
	High Speed HDMI with Ethernet
	HDCP 1.4
	HDCP 2.2
Supported operating system:	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Windows 10 Mobile
	Mac ex OS 10.12
	Android ex 6.0
	Chrome OS
	Linux ex Kernel 4.3
Interface	
Output:	1 x HDMI-A 19 pin female
Input:	1 x USB Type-C™ female (power supply)
	1 x USB Type-C™ male
Technical characteristics	
Chipset:	Parade PS176
	VIA VL100
Maximum screen resolution:	4096 x 2160 @ 60 Hz
Signal transmission:	video
	audio
Physical characteristics	
Ferrite core:	1 x
Housing material:	Aluminium
Cable length:	20 cm
Connector finishing:	nickel-plated
Colour:	dark grey