





Made for the latest UHS-II SD cards

The RDF9 UHS-II Card Reader with the latest UHS-II interface is here to unleash the high speed performance of a UHS-II SD card, transferring high resolution RAW images and HD videos to your computer just in seconds. In addition, it is backward compatible with UHS-I and any other SDXC and SDHC SD cards.



Blazing-fast transfer speeds ever

Taking full advantage of USB 3.1 and UHS-II technology, the read and write speeds of the RDF9 are up to 260MB/s and 190MB/s accordingly. When paired with a 32GB Transcend's UHS-II SD card, the RDF9 only takes 38 seconds to transfer an 8GB of video file.



A must-have for professionals

High speed boosts your workflow and efficiency. The versatile RDF9 lets professional photographers, videographers and graphic designers transfer data at high speed, accelerating the entire post-production processing.





USB 3.1 Gen 1 Card Readers **RDF9**

Features

- · USB 3.1 Gen 1 interface
- Supports high-speed UHS-II SD memory cards
- Multifunctional card reader with SD, microSD, and CompactFlash card slots
- Designed for high-resolution video, raw image transfers, and post-production processing
- Download the RecoveRx data recovery software from Transcend's official website



RecoveRx software

Transcend's RDF9 card reader includes RecoveRx software – a user-friendly application that allows you to conduct an in-depth search within your storage device for traces of erased data that can be recovered.

Specifications			
Appearance			
Dimensions (Max.) 67.6 mm x 45 mm x 15.2 mm (2.66" x 1.77" x 0.60")			
Weight (Max.)	30.6 g (1.08 oz)		
Color	Black		
Interface			
USB Type	micro USB to USB Type A		
Connection Interface	USB 3.1 Gen 1		
Hardware			
Card Reader Slot(s)	SD/microSD/CompactFlash		
Operating Environme	ent		
Operating Temperature	0°C (32°F) ~ 70°C (158°F)		
Operating Voltage	5V		
Performance			
Note	Speed may vary due to host hardware, software, usage, and		

Note	Speed may vary due to host hardware, software, usage, and
	storage capacity.

Warranty

_	
Certificate	CE/FCC/BSMI/KC/RCM
Warranty	Two-year Limited Warranty

System Requirement

Operating System	Microsoft Windows 7
	Microsoft Windows 8
	Microsoft Windows 10
	Mac OS X 10.2.8 or later
	Linux Kernel 2.6.30 or later

Compatibility

Memory Card Supported	SDHC (UHS-II)/SDXC (UHS-II)/SDHC (UHS-I)/SDXC (UHS-I)		
	microSDHC (UHS-I)/microSDXC (UHS-I)		
	CompactFlash (UDMA6)/CompactFlash (UDMA7)		

Ordering Information

TS-RDF9K2

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



USB 3.1 Gen 1 Card Readers Comparison	⊕ Transcend	⊕ Transcend	⊕ Transcend	17 Transcend 15 Transcend	Transcend Transcend
	RDC8	RDF9	RDF2	RDF8	RDF5
Appearance					
Dimensions (Max.)	67.6 mm x 45 mm x 15.2 mm (2.66" x 1.77" x 0.60")				56 mm x 24 mm x 8.9 mm (2.20" x 0.94" x 0.35")
Weight (Max.)	32 g (1.13 oz)	30.6 g (1.08 oz)	26 g (0.91 oz)	32 g (1.13 oz)	18 g (0.63 oz)
Color	Black	Black	Black	Black/White	Black/White/Pink
Interface					
USB Type	micro USB to USB Type C	mi	icro USB to USB Ty	ne A	USB Type-A
Connection Interface	Timero osa to osa type e	oss type n			
			USB 3.1 Gen 1		
Hardware					
Card Reader Slot(s)	SD/microSD CompactFlash	SD/microSD CompactFlash	CFast	SD/microSD CompactFlash	SD/microSD
Warranty					
Warranty		Two	o-year Limited War	rantv	
Compatibility					
Memory Card Supported	SDHC (UHS-I)	SDHC(UHS-II)	CFast 2.0	SDHC (UHS-I)	SDHC (UHS-I)
	SDXC (UHS-I)	SDXC (UHS-II)		SDXC (UHS-I)	SDXC (UHS-I)
	microSDHC (UHS-I)	SDHC(UHS-I)		microSDHC (UHS-I)	microSDHC (UHS-I)
	microSDXC (UHS-I)	SDXC (UHS-I)			microSDXC (UHS-I)
	CompactFlash (UDMA7) r			CompactFlash (UDMA7	')
		microSDXC (UHS-I)			
		mpactFlash (UDMA6)			
	Col	mpactFlash (UDMA7)			
SD UHS-II	-	~	-	-	-
SD UHS-I and below	✓	~	-	<u> </u>	<u> </u>
microSD UHS-I and below	~	✓	-	✓	<u> </u>
CompactFlash UDMA5 and below		~	-	~	-
CompactFlash UDMA7 & UDMA6	~	~	-	~	-
CFast 2.0 and below	-	-	<u> </u>	-	-

Note: Simultaneous insertion of two cards not supported.