

FX-890II

DATASHEET / BROCHURE



Nine-pin dot matrix printer offering faster printing, outstanding reliability and extremely low TCO.

The FX-890II is a high-volume, low TCO 80-column dot matrix printer designed for fast, reliable printing. A contemporary new design and smaller footprint make upgrading easy and add a range of new features for unprecedented flexibility.

Market-leading print speeds¹

The FX-890II offers an improved USD (ultra speed draft) speed of 735 characters per second at 12 characters per inch, making a real difference to high-volume print runs such as stock reports and large batches of invoices or freight documents.

Outstanding reliability

Epson's dot matrix technology is already mature and very reliable, and these new printers improve the mean time between failure by 25% to 25,000 power-on hours, ideal for challenging conditions or where regular maintenance is not practical.

Smaller footprint

Epson's new range of dot matrix printers has a refreshed design with a smaller footprint - depth has been reduced to just 320mm - making it easy to place into a business environment.

KEY FEATURES

- **Market-leading print speeds**
Complete high-volume print runs even faster
- **Very low TCO**
Cheap, long-lasting consumables and low power use
- **Even better reliability**
Improved by 25% to 25,000 power-on hours
- **Smaller footprint**
Allows for easy placement within a business environment
- **Energy Star compliant**
To ensure the best possible energy efficiency

PRODUCT SPECIFICATIONS

TECHNOLOGY

| | |
|-------------------|------------|
| Number of Pins | 9 pins |
| Number of columns | 80 columns |

PRINT

| | |
|------------------|---|
| Printing Speed | HighSpeed-Draft: 10 cpi: 612 chars/s, Draft: 10 cpi: 463 chars/s, NLQ: 10 cpi: 115 chars/s |
| Barcodes | Coda bar (NW-7), Code 128, Code 39, Industrial 2 of 5, Matrix 2 of 5, POSTNET, UPC-A, UPC-E |
| Carbon Copies | 6 plus one original |
| Character Tables | PCAPTEC, PC437, PC720, PC850, PC858, ISO-8859-15, Roman 8, Italic |
| Character Sets | 42 |

CONNECTIVITY

| | |
|------------|---|
| Interfaces | USB - compatible with USB 2.0 specification, Bidirectional parallel |
|------------|---|

PAPER / MEDIA HANDLING

| | |
|----------------------------------|---|
| Document Feed | Single sheet front and rear, Continuous paper front and rear, Paper output rear |
| Paper Formats | Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes, Cardboard |
| Paper Thickness Continuous Paper | 0,46 mm |
| Paper Thickness Label Base Sheet | 0,46 mm |
| Paper Thickness Multi Part | 0,12 mm - 0,46 mm |
| Paper Thickness Single Sheet | 0,06 mm - 0,14 mm |

GENERAL

| | |
|----------------------------|---|
| Energy Use | 54 W, 0,5 W (economy), 8 W (standby) |
| Supply Voltage | AC 198 V - 264 V |
| Energy Star | Yes |
| Product dimensions | 414 x 320 x 177 mm (Width x Depth x Height) |
| Product weight | 7,2 kg |
| Temperature | Operation 5° C - 35° C, Storage -30° C - 60° C |
| Mean Time Between Failures | 25.000 Hours |
| Print Head Life | 400 Million Strokes/Wire |
| Fonts | Bitmap font EPSON Draft (10 CPI, 12 CPI, 15 CPI), Bitmap font EPSON OCR-B (10 CPI), Bitmap font EPSON Roman (10 CPI, 12 CPI, 15 CPI, Proportional), Bitmap font EPSON Sans Serif (10 CPI, 12 CPI, 15 CPI, Proportional) |
| Ribbon Yield | 7 characters Black Draft |

OTHER FEATURES

| | |
|-------------------|-----------------|
| Emulations | ESC/P, IBM PPDS |
| Input Data Buffer | 128 kB |

OTHER

| | |
|----------|---|
| Warranty | 12 months Carry in Optional warranty extension available |
|----------|---|

LOGISTICS INFORMATION

| | |
|-------------------|---------------|
| SKU | C11CF37401 |
| EAN code | 8715946634487 |
| Country of Origin | Indonesia |

FX-890II

WHAT'S IN THE BOX

- Driver and utilities (CD)
- User guide
- AC cable
- Ribbon

SUPPLIES

- Epson SIDM Black Ribbon Cartridge for FX-890, FX-890A (C13S015329) (C13S015329)

OPTIONAL ACCESSORIES

- SIDM FX-890II, LQ-590II Pull Tractor Unit C12C933761
- Epson SIDM Paper Roll Holder for LX-300-II/1170II, FX-890/A, FX-2190, LQ-690/300+II series C12C811141

Epson Deutschland GmbH
Otto-Hahn-Str. 4
D-40670 Meerbusch
Info-Line: 02159 92 79 500
Telefax: +49 (0) 2159/538-3000
www.epson.de

Epson in Österreich
Info-Line: 01 253 49 78 333
www.epson.at
Epson in der Schweiz
Info-Line: 022 592 7923
www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.
Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

1. Speeds compared with published specifications for directly competing products, May 2017.

EPSON[®]