



Delock USB Type-C™ 3.1 Docking Station HDMI 4K 30 Hz, Gigabit LAN and USB PD function

Description

This docking station by Delock can be connected to a computer with a USB-C™ Alt-Mode or Thunderbolt™ 3 port and provides a variety of interfaces. A display can be operated at the HDMI output. Two built-in USB Type-A ports allow the use of peripherals, and connections for gigabit network, as well as an SD card reader, complete the features. With a USB-C™ power supply, laptops such as the Macbook or Chromebook can be charged during operation.



Specification

- Connectors:
 - 1 x Gigabit LAN 10/100/1000 Mb/s RJ45 jack
 - 1 x HDMI-A 19 pin female
 - 1 x USB Type-C™ PD female (power supply)
 - 2 x USB 3.0 Type-A female
 - 1 x SD / SDHC / SDXC / MMC slot
 - 1 x USB Type-C™ male
- Chipset: VL813, VL100, GL857L, PS176, RTL8153
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Output power: 4.5 W per port (5 V / 0.9 A)
- Input power: 1 x USB Type-C™ female max. 60 W (20 V / 3 A)
- Metal housing
- Cable length incl. connector: ca. 15 cm
- Colour: anthracite
- Dimensions (LxWxH): ca. 116 x 46 x 16 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, Linux ex Kernel 4.9, Mac ex OS 10.12
- Device with a free USB Type-C™ port and Displayport alternate mode or with a free Thunderbolt™ 3 port

Package content

- USB-C™ docking station
- User manual

Item no. 87721


EAN: 4043619877218

Country of origin: China

Package: Retail Box



Images



**General**

Specification:	High Speed HDMI
Supported operating system:	Chrome OS Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows 10 Mobile ex Linux Kernel 4.9 ex Mac OS 10.12
Supported memory card:	SD

Interface

Output:	1 x RJ45 jack 1 x HDMI-A 19 pin female 1 x SD slot 2 x USB 3.0 Type-A female
Input:	1 x USB Type-C™ female (power supply) 1 x USB Type-C™ male

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 30 Hz
Signal transmission:	video audio
Voltage:	USB bus powered 1 x USB Type-C™ Power Delivery female (optional for power supply)

Physical characteristics

Housing material:	Aluminium
Cable length incl. connector:	15 cm
Length:	116 mm
Width:	46 mm
Height:	16 mm
Colour:	anthracite