

Eaton EVMIF132X

Catalog Number: EVMIF132X

Eaton Metered Input G4 Rack PDU, 0U, 39U, IEC-60309 input, 3m cord, 1ph, 7.4kW, 32A, 200-240V, 42 outlets (24)C13, (18)C39

General specifications



Product Name	Catalog Number
Eaton Rack PDU G4	EVMIF132X
Model Code	EAN
PDU G4 MI 0U 309 32A 1P 24xC13,18xC39	3553340697135
	Product Length/Depth
	1 mm
Product Height	Product Width
1 mm	1 mm
Product Weight	Warranty
1 kg	3 year
Compliances	Certifications
CB	IEC 62368-1
LVD Directive	EN IEC 63000
RoHS Directive	CISPR 35/EN 55035
WEEE Directive	CE
Packaging Directive	EAC
	UKCA
	Cm
	Ukr
	IEC/EN 61000-6-2
	IEC/EN 61000-6-4
	IEC 61000-3-11
	IEC 61000-3-12

Product specifications

Electrical connection

Connecting cord with plug

Wattage

7.4 kW max

Form factor

0U (Vertical)

Mounting direction

Vertical

Number of Outputs 6-20R

0

Number of Outputs C20

0

Amperage Rating

32 A

Input connection

IEC-60309 32A 1Ph

Num of Outputs PC (SCHUKO)

0

Number of Outputs L14-30R

0

Frequency rating

50/60 Hz

Evaluation

At distance

Operating Temperature

0° to 60°C (32° to 140°F)

Number of outlets with earth pin

42

No of Outlet Suisse Stndrd Type25

0

Mass configuration

Yes

No of Outlet Suisse Stndrd Type23

0

Special features

Resources

Brochures

[Rack PDU G4 Brochure EN](#)

Remote Site Management
Versatile C39 outlet
supports C14 or C20 power
cord plug
High retention outlets
designed to securely fit
standard power cords and
support P-Lock power cords
Cybersecurity standards UL
2900-1 and IEC 62443-4-2
Hot-Swap network control
module
Network Cascading, connect
up to 32 PDUs via network
loop
Power sharing between two
network modules PDUs
ensures constant access to
PDU data & sensors
1% IEC Class 1 billing grade
measurement accuracy
Gigabit network card with 2x
Gb ports
Support protocols RestAPI,
Modbus TCP, SNMP, LDAP,
HTTPS
Optional sensor
Temperature/Humidity

Cord length

3m

Number of Outputs 6-15R

0

Color

Black

SNMP

Yes

Over voltage category

2

Outlets

(24) C13, (18) C39

Number of Outputs L6-30R

0

Number of Outputs 5-20R

0

Number of UK BS1363 sockets

0

Number of Outputs 5-15R

0

Number of Outputs L5-30R

0

No of Outlet Suisse Stndrd Type15

0

Number of Outputs C13

24

No of Outlet Suisse Stndrd Type13

0

Phase

Single-phase

Mounting dimension (standardized)

Metric

Accessories

Rack PDU

Rack mounting accessories

Quickstart guide

Safety Instructions

Number of outputs hardwired

0

Number of outputs (other)

18

Ethernet interface

Yes

Number of Outputs C19

18

Outlet control

No

Switchable

No

Input voltage

200-240V

Material

Aluminium

Number of Outputs L6-20R

0

Series

G4

Type

Metered input Rack PDU

Serial interface

Yes

Mounting Dimension (metrical)

52

Number of Outputs L5-20R

0



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)