

# Vero B7-Serie

# Vero B247YGbmiprzx

Environmentally friendly in everyday business

The Vero B7 series impresses with a unique design paired with all the features that a modern business monitor must have. The ZeroFrame design convinces all along the line and enables a seamless multi-monitor setup without disturbing frames. Thanks to the flexibly adjustable Ergo-Stand, the monitors of the B7 series can be adjusted in height and rotated by 90° (pivot function) - all in the name of ergonomics. This series is ENERGY STAR®, TCO and EPEAT certified, reflecting Acer's commitment to environmental protection. It is made of up to 85% post-consumer recycled (PCR) plastic, up to 5% OBP (Ocean Bound Plastic) and uses 100% recyclable packaging.



- Diagonal size: 60.5 cm (23.8 inches)
- Resolution: 1920x1080
- Response time: 4ms (GTG), 1ms(VRB)
- Brightness: 250 cd/m<sup>2</sup>
- Signal input: 1x VGA, 1x HDMI (1.4), 1x DP, USB 3.2 x4 +USB-B (1up 4down), Audio In/Out













### Vero B247YGbmiprzx

#### SPECIFICATIONS



#### Technical Specifications

Diagonal size Active display area (WxH) Aspect ratio Resolution Panel type Response time Brightness Backlight type Acer CrystalBrite Viewing angle (h/v) CR>10:1 Static contrast ratio Dynamic contrast ratio Colors Colour space Speaker Signal input

Chassis colour Frequency (H/V)

Refresh rate (max.) HDMI DisplayPort VGA DVI USB 3.1 Type-C USB Hub Audio

#### Power supply and consumption

Power supply EPREL No. Energy Efficiency Class On-mode Power Standby mode Power Off mode Power

LED No, anti-reflective display 178/178° 1500:01:00 100M:1 16.7M 99% sRGB 2 x 2 watts 1x VGA, 1x HDMI (1.4), 1x DP, USB 3.2 x4 +USB-B (1up 4down), Audio In/Out Black HDMI:30~140K / 48~120, DP:140~140K / 48~120, VGA:30~85K / 48~75 120Hz HDMI/DP, 75Hz VGA 1x HDMI (1.4) 1x (DP 1.2) Yes USB 3.2 x4 +USB-B (1up 4down) 1x

60.5 cm (23.8 inches)

4ms (GTG), 1ms(VRB)

527x296 mm

1920x1080

250 cd/m<sup>2</sup>

IPS Technology

16:09

2067532 11,8 kWh/1000h 0,5 W 0,3 W

Internal

С

#### ErgoStand

Tilt angle Swivel angle Height adjust range Pivot function VESA wall mounting -5°~35°

#### Norms and Standards

Warranty Certification EPEAT

MTBF

#### Dimensions and weight

Dimension (W x H x D) Dimension w/o stand (W x H x D) Weight (unpacked) Package Dimensions Weight (packed) Weight w/o stand Pallet qty and size (H  $\times$  W  $\times$  D) Container qty (20'/40')

## Others

OSD languages Operating ambient temperature Operating ambient humidity Storage ambient temperature PCR / OBP Kensington Security Slot

EN, DE, ES, NL, FR, IT, FI, RU, P, CN, PL 5°C bis 35°C 10% bis 85% -20°C to 60°C PCR 85% + OBP 5% Yes

36 months Carry In

30,000 hrs. at 25°C

gyStar

5,33 kg

3,07 kg

8 kg

63x42x1670

600/1.200

EPEAT Gold

TCO Edge, Win 10 compliant, TUV LBL, Ener-

540.30x350.90-515.90x186.10 mm

540.30x318.20x48.70 mm

60 Pcs (115x115x222.50 cm)

#### Ordering Information

Model Product line Part number EAN

Vero B247YGbmiprzx **B7** Series UM.QB7EE.G05 4711474183941

#### Special features

Special features Acer VisionCare Yes Acer Display Widget Yes

+/-60° 165 mm +/-90° 100x100 mm

This data sheet is subject to change without notice. Availability may vary from region to region. Acer is not liable for any errors or omissions contained in the product descriptions. In addition to the standard warranty conditions, the statutory warranty regulations also apply to consumers. For more information on exclusions and limitations, please refer to our warranty conditions for the respective product. If the warranty period in the PDF document for the warranty conditions differs from the information on the Acer homepage, the information given on this website applies and not the information contained in the PDF. Copyright 2024 Acer, Inc. all rights reserved. Acer and the Acer logo are registered trademarks of Acer Incorporated. All other trademarks, registered trademarks and/or service marks mentioned or otherwise recognizable are the property of their respective owners. All prices quoted are manufacturer's suggested retail prices.