

4-Port Industrial USB 3.0 Hub - Mountable

Product ID: ST4300USBM



The ST4300USBM Mountable 4-Port Industrial USB Hub (USB 3.0) offers a simple way to expand a systems current USB capability by providing 4 additional external USB 3.0 ports from a single USB 3.0 host connection, with speeds up to 5 Gbps.

Designed for extreme operating environments, this industrial-grade hub provides reliability under almost any condition and can be securely mounted to most surfaces.

Fully compliant with the SuperSpeed USB 3.0 specification, this industrial USB hub is backward compatible with USB 2.0 and 1.x specifications for simultaneous support of older USB peripherals or even older systems without USB capabilities.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.



Certifications, Reports and Compatibility



Applications

- Locations where the hub needs to be securely mounted to a surface, such as a wall or under a desk
- Environments subject to large temperature variances or where physical damage may occur, such as within a factory
- Heavily trafficked areas where there is a concern for the USB cables becoming unplugged

Features

- SuperSpeed USB 3.0 compliant, supporting transfer rates up to 5 Gbps
- Backwards compatible with USB 2.0 and 1.x specifications and devices
- Fully supports USB 3.0 and 2.0/1.x devices simultaneously
- Support for screw-locking USB cables (sold separately)
- Internal dual-regulator power circuits provide up to 900mA of stable and reliable power per port
- Bus power, coaxial power adapter and terminal block style power input options supported
- All metal construction
- Built-in surface mounting brackets
- Plug-and-Play and hot-swap compatible

Hardware	Warranty	2 Years	
	Chipset ID	VIA/VLI - VL811+	
	Fast-Charge Port(s)	No	
	Interface	USB 3.0	
	Ports	4	
	USB-C Device Port(s)	No	
	USB-C Host Connection	No	
Performance	Maximum Data Transfer Rate	5 Gbps	
	MTBF	245,881 Hours	
Connector(s)	External Ports	1 - Terminal Block (2 Wire) 1 - USB Type-B (9 pin) USB 3.0 Female 4 - USB Type-A (9 pin) USB 3.0 Female	
	Software	OS Compatibility	OS Independent; No additional drivers or software required
	Special Notes / Requirements	System and Cable Requirements	Available USB 3.0 port
Indicators	LED Indicators	1 - Power (Red) 4 - USB Device Connection (Green)	
	Power	Center Tip Polarity	Positive
Output Current		3A	
Output Voltage		12 DC	
Plug Type		M	
Power Consumption (In Watts)		36	
Power Source		AC Adapter Included	
Environmental	Humidity	5~95% RH	
	Operating Temperature	0°C to 55°C (32°F to 131°F)	
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)	
Physical Characteristics	Color	Black	
	Enclosure Type	Steel	
	Form Factor	Industrial	
	Product Height	0.9 in [23.5 mm]	
	Product Length	6 in [152 mm]	

	Product Weight	16.9 oz [480 g]
	Product Width	2.3 in [59.6 mm]
Packaging Information	Shipping (Package) Weight	47.7 oz [1350 g]
What's in the Box	Included in Package	1 - Industrial USB 3.0 Hub 1 - USB 3.0 cable (non-locking) 1 - Universal Power Adapter (NA/JP, EU, UK, ANZ) 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.