

USB 3.1 Active Cable A/B, 10m

No.: 43098



Description

- USB 3.1 / USB 3.0 Active Cable - contains electronics
- USB 3.1 Gen 1 / USB 3.0 SuperSpeed Standard (5Gbps)
- Connections: USB Type A male to USB Type B male
- Plug and play
- USB Bus Powered
- Chipset: GL3521

Technical details

Connectors

- Connector A: USB Type A Male
- Connector B: USB Type B Male
- Power: -
- Housing Material: Plastic
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Nickel
- Dimensions (approx.) WxDxH:
 - USB A Male: 16x49x9mm (0.63x3.7x0.35in)
 - USB B Male: 10x52x13mm (0.39x2.05x0.51in)
 - Repeater (2x): 35x100x15mm (1.26x3.94x0.59in)

Cable Construction

- Length: 10m (32.8ft)
- Standard: USB 3.1 Gen 1 / 3.0
- Colour: Black
- Type: Round
- Jack Diameter: 7mm +/- 0.15mm (0.28in +/- 0.01in)
- Jack Material: PVC
- Conductor Material: Copper
- Conductor Gauge: 28/28/22AWG
- Shielding: 85% Aluminium

Specifications

- Supported Bandwidth: 5 Gbps
- Nominal Attenuation:
 - 100 MHz, -1.5 dB
 - 1.25 GHz, -5.0 dB
 - 2.5 GHz, -7.5 dB
 - 7.5 GHz, -25 dB
- Minimum Bend Radius: 60mm (2.36in)
- Maximum Tensile Load: -
- Operating Temperature: 0°C - 55°C (32°F - 131°F)

- Storage Temperature: -20°C - 85°C (-4°F - 185°F)
- Transmission Medium: Twisted Pair
- Transmission Technology: USB 3.0

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 300x300x80mm (11.81x11.81x3.15in)
- Netto Weight: 0,5 (1.1lb)
- Gross Weight: 0.530kg (1.17lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Packaging Content

- USB 3.0 Active Cable 10m
- Lindy Manual

Purchasing Information

- No.: 43098
- EAN: 4002888430982

© LINDY 2018