

# Eaton 5P650IG2

Catalog Number: 5P650IG2

Eaton 5P UPS, 650 VA, 520 W, Input: C14, Outputs: (4) C13, Tower



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton 5P Gen2 UPS	5P650IG2
<b>EAN</b>	<b>Product Length/Depth</b>
3553340710254	345 mm
<b>Product Height</b>	<b>Product Width</b>
233 mm	150 mm
<b>Product Weight</b>	<b>Warranty</b>
7.9 kg	3 year on electronics, 2 year on battery
<b>Compliances</b>	<b>Certifications</b>
LVD Directive (CB)	IEC/EN 62040-1
EMC Directive	IEC/EN 62040-2
RoHS Directive	IEC/EN 62040-3
WEEE Directive	UL 1778
Packaging Directive	CSA-C22.2
Batteries Directive	CE
	UKCA
	Cm
	Ukr
	KCC
	cTUVus
	BIS

### Special features

Automatic Voltage Regulation (AVR)  
Energy efficient, reduce energy and cooling costs  
Delivers clean sinewave output  
1 slot for optional com card (Network management card, Relay card or Network and Industrial card)  
Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)  
Fully integrates with Eaton Brightlayer Software suite  
1 USB port + 1 serial port  
Advanced Battery Management (ABM+) technology to increase battery lifetime and improve life time prediction accuracy  
Next-generation graphical LCD display  
Hot swappable batteries  
Remote reboot and runtime optimization thanks to 2 manageable outlet groups  
Remote ON/OFF and remote Power OFF connectors

### Type

UPS

### Topology

Line-interactive

### Form factor

Tower

### Construction type

Free standing model

### Color

Black/silver

#### Enclosure

Black/silver

#### VA rating

650 VA

#### Wattage

520 W

#### Rack mounting kit

No

#### Package contents

USB cable

(2) IEC-IEC cables

Quickstart guide

Safety instructions

#### Auto shutdown function

Yes

#### Primary frequency - max

70 Hz

#### Primary frequency - min

47 Hz

#### Input connection

C14

#### Input nominal voltage

230V default (200/208/220/230/240V)

#### Nominal frequency

50-60 Hz

#### Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in low sensitivity mode

#### Receptacle

(4) C13

#### Number of Outputs C13

4

#### Output waveform

Sine wave

#### Voltage

230V

#### Output nominal voltage

230V default (200/208/220/230/240V)

#### Feed type

1

#### Voltage type

AC

#### Runtime graph

\$row.attributeValue.cdata

#### Battery management

ABM or constant voltage charging method (user selectable),  
automatic battery test, deep discharge protection

#### Battery replacement

User replaceable

#### Battery rating

12 V / 9 Ah

#### Battery type

Lead-acid maintenance-free (replaceable)

#### Extended battery capability

No

#### Runtime at half load

9 min

#### Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for  
remote On/Off and Remote

Power Off

Dry contacts (2 outputs,  
optocoupler, RJ)

#### Expansion slots

One slot for optional communication card

#### Ethernet interface

No

#### Includes network card

No

#### Software compatibility

Eaton Brightlayer Software suite

#### User interface

Multilingual graphical LCD display

#### Type of interface

Other

#### Potential free switch contact

Yes

#### Altitude

3000 m

#### BTU Rating

Online: 53, Battery: 461 BTU/hr

#### Noise level

<35 dB at 1 meter

#### Relative humidity

0-90% non-condensing

#### Temperature range

0-90% non-condensing

#### Input voltage - max

294 V

#### Input voltage - min

150 V

#### Output voltage - max

240 V

#### Output voltage - min

200 V

#### Secondary frequency - max

60 Hz

#### Secondary frequency - min

50 Hz

#### Battery quantity

1

#### Efficiency

97

#### Input voltage range

160-294 V (adjustable to 150 V-294 V)

#### Output frequency

50/60 Hz

#### Output power factor

0,8

#### Output voltage range

230 V (+6%/-10%)

Phase (input)

1

Phase (output)

1

Runtime at full load

1



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)