



TL-D800C

Laufwerksschacht	8 x 3,5-Zoll SATA 6Gb/s, 3Gb/s
Laufwerkskompatibilität	3,5-Zoll SATA Festplattenlaufwerke 2,5-Zoll SATA Festplattenlaufwerke 2,5-Zoll SATA SSDs
Audio Alert On/Off Switch	Yes
Formfaktor	Tower
Host Schnittstelle	1 x USB 3.2 Gen 2 Type-C
LED-Anzeigen	HDD 1-8, Status, Link, Lüfterfehler
Tasten	Netzschalter
Abmessungen (HxBxT)	188,2 × 329,3 × 281,4 mm
Gewicht (netto)	6.18 kg
Gewicht (brutto)	7.54 kg
Max. Anzahl unterstützter HDDs/SSDs	8
Festplattentyp	3,5-Zoll SATA Festplattenlaufwerke 2,5-Zoll SATA Festplattenlaufwerke 2,5-Zoll SATA SSDs
Betriebstemperatur	0 - 40 °C (32°F - 104°F)
Relative Luftfeuchtigkeit	5 – 95% relative Luftfeuchtigkeit / nicht kondensierend, Feuchtkugeltemperatur: 27°C (80,6°F)
Netzteil	250W PSU, 100 - 240V
Stromverbrauch: Betriebsmodus, typisch	48,4 W
Fan Mode Switch	Yes (Auto, hoch, mittel, niedrig)
Lüfter	2 x 120mm, 12VDC
Geräuschpegel	26,2 db(A)
Systemwarnung	Buzzer

Kensington-
Sicherheitsschloss

Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.