

Product data sheet

Specifications



APC Performance SurgeArrest 6 outlets 230V Germany

PM6-GR

Overview

Lead time

Main

Main Input Voltage	230 V
Input Connection Type	Schuko CEE 7/7P
Cable length	2.00 m
Number of cables	1
Provided equipment	User manual

Physical

Colour	White
Height	6.17 cm
Width	27.15 cm
Depth	11.03 cm
Net weight	0.69 kg
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Input power	2300 W
Network frequency	50 Hz
Maximum input current	10 A
Switching current capacity	10 A

Output

Number of power socket outlets	6
Outlet standard	Schuko CEE 7

Conformance

Product certifications	CE
------------------------	----

Equipment protection policy Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...50000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	40 dB
Peak current	48 kAcommon mode
Surge energy rate	1836 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	31 cm
Package 1 Length	16.5 cm
Package 1 Weight	0.83 kg
SCC14	10731304313714

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty Limited Lifetime (European Union countries only)

Recommended replacement(s)