



Technical Specifications

Features

A high-performance wireless repeater for wide range and high data throughput in Wi-Fi networks

Can also be connected to a router via network cable (LAN bridge)

Secure upon delivery with WPA2 encryption,

With Mesh Wi-Fi you can combine several wireless access points into one intelligent system (FRITZ!OS 6.90 or later)

Two wireless radio units: Up to 2400 Mbit/s (5 GHz) + 600 Mbit/s (2.4 GHz) for the optimal supply of multiple wireless devices

One gigabit LAN port: Connected devices (computers, printers, audio/video players, etc.) are granted Wi-Fi functionality

WPA3/2 transition mode is also available

Compatible with all common wireless routers

Simple, secure configuration at the touch of a button (WPS method)

Display shows connection quality and status

Supports the IPv6 internet protocol

Easy to install

Optimized for use with all FRITZ!Box models

Installation at the touch of a button with Wi-Fi Protected Setup (WPS)

Easy operation via browser-based user interface
(<http://fritz.repeater>)

Ports and interfaces

Wireless access point: compatible with all wireless routers with the 802.11 ax/ac/n/g/a wireless standards

1 x Gigabit LAN port (10/100/1000 Mbit/s)

Connection to mains via 230 V, 50 Hz

Wi-Fi: 2400 Mbit/s (5 GHz, 2 x 2, 160 MHz) + 600 Mbit/s (2,4 GHz, 2 x 2, 40 MHz)

Package contents

FRITZ!Repeater 1200 AX
Printed quick guide

Slim Ethernet cable
Euro to CEE 7/4 (Schucko) adapter (pre-mounted)

Device properties

Dimensions (W x D x H)
approx. 80 x 80 x 37 mm (without the plug)

Weight: approx. 160 g

Power consumption:
approx. 4 watts, 8.4 watts maximum

Article number

20002974