

# Fiche technique du produit

Spécifications



## NetShelter WX 13U w/Threaded Hole Vertical Mounting Rail Vented Front Door

AR100HD

Statut commercial : Commercialisé

### Présentation

#### Présentation

Ideal for retail, healthcare, and educational facilities, the wall rack offers an efficient solution for deploying server and networking equipment for edge computing applications. For areas with limited floor space. Designed to house your server, as well as network solutions such as network switches and patch panels. Rack hinges at the rear allowing for access to the back of the rack during installation and setup or while undergoing maintenance. The door is reversible allowing for the door to open direction desired to avoid interference with its surroundings. Optional 120V fan tray top-mounted and caster kit. Several APC Smart-UPS models low-profile provide easy UPS integration and mounting. 13U Wall mount cabinet, 19 inches maximum mounting depth, 200lb weight capacity, 19" rack width, ships fully assembled, vented door, 5 year APC warranty.

#### Lead time

### Principales

Nombre d'unité de rack	13U
Nombre de câbles	1
Équipement fournis	Touche(s) Manuel utilisateur Modèle de fixation murale

### Physique

Hauteur	66,3 cm
Largeur	58,4 cm
Profondeur	63,1 cm
Poids du produit	42,73 kg
Couleur	Noir
Montage préconisé	No preference
Mode d'installation	Non montable en rack
Profondeur de montage maximale	48,26 cm
Largeur du rack	19"
Marquage	Calibre 16 rail de montage EIA Calibre 16 porte avant Calibre 16 poste Calibre 13 porte arrière Calibre 18 toit Calibre 18 panneaux latéraux
Charge permanente admissible	90,72 kg statique

## Conformité

Normes	EIA-310E
--------	----------

## Emballage

Type d'emballage 1	PCE
--------------------	-----

Nb produits dans l'emballage 1	1
--------------------------------	---

Hauteur de l'emballage 1	83,8 cm
--------------------------	---------

Largeur de l'emballage 1	68,6 cm
--------------------------	---------

Longueur de l'emballage 1	77,5 cm
---------------------------	---------

Poids de l'emballage 1	52,17 kg
------------------------	----------

## Durabilité de l'offre

Statut environnemental de l'offre	Produit Green Premium
-----------------------------------	-----------------------

Régulation REACH	<a href="#">Déclaration REACH</a>
------------------	-----------------------------------

Sans SVHC REACH	Oui
-----------------	-----

Directive RoHS UE	Conformité pro-active (Produit en dehors du scope légal RoHS UE) <a href="#">Déclaration RoHS UE</a>
-------------------	---

Sans métaux lourds toxiques	Oui
-----------------------------	-----

Sans mercure	Oui
--------------	-----

Information sur les exemptions RoHS	<a href="#">Oui</a>
-------------------------------------	---------------------

Take-back	Take-back program available
-----------	-----------------------------

## Garantie contractuelle

Garantie	5 ans réparation ou remplacement
----------	----------------------------------

## Remplacement(s) recommandé(s)