



# I1601FWUX

**15.6 inch**

(39.6 cm) LCD MONITOR

## USB-C



One cable is all you need. The USB-C technology carries both the power and the display signal to the screen in one cable. It not only looks ultra-clean and sleek but also greatly improves portability of

the monitor.

## Productivity anywhere you go



More screen real-estate significantly increases productivity. With I1601FWUX, connected to your laptop you can be efficient even outside your home or office – when travelling or, visiting customers.

### ▣ Auto-Pivot

Change the orientation of the monitor to automatically align screen content (included AOC i-Menu software needed to activate).

## Portable, elegant solution



The I1601FWUX looks gorgeous and is durable with its metal alloy case. While being just 8.5 mm thick and weighing ultra-light 800 g it is easy to travel with for work or study. It also easily fits in most notebook bags.

## Smart cover



The included smart cover protects your display inside or outside your bag against dirt and damage. When the display is in use, the cover acts as a flexible screen holder, in portrait or landscape mode.

### ▣ USB C Video

Screen Details

Color	Black
Resolution	1920x1080 PX
Refresh rate	60Hz
Response time	5 ms
Panel	IPS
Backlight	WLED
Aspect ratio	16:9
Brightness (typical)	220 cd/m²
Pixel Pitch (H) (V)	0.179
Diagonal (inch)	15.6 inch
Active Screen Area (HxW)	344.23 x 193.54 mm
Viewing angle (CR10)	160/160 °
Display Colours	262.000
low_blue_light	✓

Connections

Signal Input	USB-C
USB input	USB C x 1

What's in the box

USB cable (1,8 m),

Sustainability

- Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Ergonomics

Tilt	+5° ~ +25° °
------	--------------

Power details

Powersupply	Internal
Power Consumption	On 8 watt, Standby 0.5 watt,

Dimensions

Product Dimensions (incl base)	376.2x235.2x8.5 mm
CartonDimensions	84x295x442 mm
Net Weight (excl package)	0.824 Kg
Gross Weight (incl package)	1.574 Kg

Warranty

WarrantyPeriod	3 Years
EAN	4038986156479

Regulations

Rohs compliant 1, Reach compliant 1,