



# 10m Cat.6 U/UTP LSZH Network Cable, Grey

Part No.: 45407

## **Description**

- Twisted Pair Patch Cable with RJ45 connectors and Test Report (100% Test)
- Cat.6 U/UTP, LSZH
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Cat.6 U/UTP LSZH network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz. The unshielded version (U/UTP) can be used for Gigabit Ethernet thanks to the special design of the electrophysical parameters (NExT, FExT, etc.) despite the lack of shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The halogen-free sheath material of the LSZH cable makes the product suitable for use in public spaces with its low smoke emission and elimination of toxic halogen emissions.

Available lengths: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Available colours: Grey, Blue, Red, Black.

### **Technical details**

#### Connectors

Connector A: RJ45 MaleConnector B: RJ45 Male

Housing Material: Polycarbonate

Connector Plating: -Pin Construction: BrassPin Plating: Gold plated

Dimensions (approx.) WxDxH: 11.6x21.5x8.3mm (0.46x0.85x0.33in)

#### Cable Construction

• Length: 10m (32.81ft)

Colour: GreyType: Cat.6

• Jacket Diameter: 6.0mm (0.24in)

Jacket Material: LSZH
Conductor Material: Copper
Conductor Gauge: 26AWG
Shielding: Aluminium / Polyester

### **Specifications**

Supported Bandwidth: 250MHz

Nominal Attenuation: 38.3dB/100m @250MHz

• Minimum Band Radius: 18.0mm (0.71in)

Operating Temperature: -25°C - 60°C (-43F - 140°F)
Storage Temperature: -25°C - 60°C (-43F - 140°F)

#### Miscellaneous

Packaging Type: PolybagWarranty (Years): 10

· Certificated: RoHS, REACH, UL

### **Purchasing Information**

• No.: 45407

• EAN: 4002888454070

#### This product is also available in other lengths

• 45400 - 0.3m (0.98ft)

- 45401 0.5m (1.64ft)
- 45402 1m (3.28ft)
- 45403 2m (6.56ft)
- 45404 3m (9.84ft)
- 45405 5m (16.44ft)
- 45406 7.5m (24.61ft)
- 45407 10m (32.81ft)
- 45408 15m (49.21ft)
- 45409 20m (65.62ft)
- 45410 30m (98.43ft)

## © LINDY 2021