


Key **Features**

- Write Away quick-start annotation, enhanced by 50-point touch and palm rejection for precise writing.
- 70W total output power speaker system with built-in 8-microphone array, for rich, immersive audio.
- EDLA-Certified with Android 14, integrated ViewSonic Education Software for seamless functionality.
- NFC and SSO sign-in for swift access to the intuitive launcher and personal settings.
- EPEAT Silver certified for enhanced energy efficiency and sustainability.



Product **Description**

Bring energy-efficient performance to your classroom with the ViewBoard® IFP51 Series, available in sizes from 55" to 98" to suit any setup. Seamless interactivity is at your fingertips, thanks to its ultra-responsive 50-point touch technology and instant 'write away' annotation. Powered by Android 14 and EDLA-Certified, it offers secure access to Google Play apps, while NFC and SSO sign-in ensure instant access to personalized settings. Integrated ViewSonic Education Software completes the experience with tools for whiteboarding, casting, and device management—delivering a more dynamic and efficient teaching experience.



Visit Us

www.viewsonic.com

Wall Mount (VESA®):

	IFP6551 Enterprise Device Licensing Agreement (E
DISPLAY	
Panel Size:	65"
Panel Type:	TFT LCD Module with DLED Backlight.
Display Area (mm):	1428.48mm(H) x 803.52mm(V) (64.5")
Aspect Ratio:	16:9
Resolution:	UHD 3840x2160
Colors:	1.07G colors
Brightness:	500 nits
Contrast Ratio:	1200:1 (typ.) / 5000:1 (DCR)
Response Time:	6.5 ms
Viewing Angles:	H = 178, V = 178 typ.
Backlight Life:	50,000 Hours (Min)
Surface Treatment:	Hardness:9H, AG+AF
Orientation:	Landscape
PLATFORM	
Processor:	Octa-Core CPU
RAM:	16GB
Storage:	128GB
TOUCH	12005
Type/ Tech:	Ultra Fine Touch Techology (IR Recognition)
Touch Resolution:	32767 x 32767
Touch Point:	EDLA/Android/Windows: 50 points of touch
	Yes
Palm Rejection:	165
INFO	x4 (Frontx2:HDMJ2.1 with CEC,HDCP; Rearx2: [(HDMJ2.1
HDMI:	with CEC, HDCP)x1+(HDMI2.1 with CEC, HDCP, ARC)x1]
RGB / VGA:	x1
DisplayPort:	x1
Audio:	x1
RS232:	x1
SD/SDHC:	TF Card Slot(Micro SD)
OPS:	x1 PC Slot
ОИТРИТ	
HDMI:	x1 (HDMI 2.1, HDCP 1.x)
Audio:	x1 (Line out)
SPDIF:	x1 (optical)
LAN	
RJ45:	x2
USB	
Type A:	x5 (Front x2 and Rear x 2 with USB3.2 Gen 1, all support
	SmartPort USB; Rear x 1 with USB 2.0 for system update)
Type B:	x2 (Front x 1 and Rear x 1 with USB3.2 Gen 1)
Type C:	x3 (Frontx1 with USB3.2 Gen 1, DP1.2, Ethernet 100M, PD 65W; Rearx1 with USB3.2 Gen 1, DP1.2, Ethernet 100M, PD 15W; Topx1 with USB3.2 Gen 1, PD 15W)
SPEAKERS	
25W x 2 front soundba	r + 20W x 1 subwoofer
MICROPHONE	
Built-in 8-array microp	10De
TOP CAMERA PLATE	
Yes	
Yes	
Yes COMPATIBILITY	
Yes COMPATIBILITY RGB PC/HDMI PC:	1920x1080 @ 60Hz
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI:	1920x1080 @ 60Hz 3840x2160
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort:	1920x1080 @ 60Hz 3840x2160 3840x2160
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAR	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE vare: myViewBoard for Android
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softw	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC)
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC)
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC) AirSync
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC) AirSync Manager
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC) AirSync Manager
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE rare: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE rare: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: Simple LAN sharing be	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE rare: myViewBoard for Android re: myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels tween IFP 10/100/1000M (USB Type-C 10/100, Android & PC
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: Simple LAN sharing be and slot-in device:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels tween IFP 10/100/1000M (USB Type-C 10/100, Android & PC 10/100/1000)
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: Simple LAN sharing be and slot-in device: Light Sensor:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels tween IFP 10/100/1000M (USB Type-C 10/100, Android & PC 10/100/1000) Yes
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: Simple LAN sharing be and slot-in device: Light Sensor: NFC Reader:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels tween IFP 10/100/1000M (USB Type-C 10/100, Android & PC 10/100/1000) Yes Yes
Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Ar BUNDLED SOFTWAI Basic Annotation Softwa Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: Simple LAN sharing be and slot-in device: Light Sensor: NFC Reader: Pen Sensor:	1920x1080 @ 60Hz 3840x2160 3840x2160 droid 14 RE are: myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels tween IFP 10/100/1000M (USB Type-C 10/100, Android & PC 10/100/1000) Yes Yes

ERGONOMICS

OPERATING CONDITIONS		
Temperature (° C):	0°C to 40°C	
Humidity:	20% ~ 80% RH non-condensing	

600 x 400

DIMENSIONS (W X H X D)

58.6 x 35.99 x 3.36 in / 1488.4 x 914.2 x 85.3 mm Physical (inch / mm): Packaging (inch / mm): 64.09 x 40.16 x 7.28 in / 1628 x 1020 x 185 mm

WEIGHT

Net (Ib / kg): 76.15 lb / 34.54 kg Gross (lb / kg): 93.28 lb / 42.31 kg

REGULATIONS

cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL(Low Blue Light Certification), Flicker Free, Green BOM, RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, PAIA

PACKAGE CONTENTS

- 1. Power Cord x1 3 meters,
- 2. USB Type-C cable x1 1.8 meters
- , USB-IF certified
- 3. USB Touch cable x1 3 meters
- 4. Touch pen (Passive pen) x 2
- 5. Quick Start Guide
- 6. RS232 adapter x1
- 7. Clamp x 5
- 8. Camera Plate x1
- 9. Screw x 8 (camera 2+2, wall mount 4)
- 10. HDMI cable x1 3meters,
- (HDMI LA certified)
- 11. Remote controller x1
- 12 AAA battery x2
- 13. Compliance statement
- 14. Warranty card (only for VSCN)

COMPATIBLE SLOT-IN PC

VPCF5-W33-G1, VPC37-W53-G1, VPC35-W53-G1, VPC-A31-O1