

Standard

SQ2H



*Actual Resolution:
3840 x 2160p

• DisplayPort(Ver. 1.2)

*1: Some functions are limited.

AAG *only applies for 43-65"

- TH-98SQ2H 700cd/m² 24.7 Operation USB Media Player Portrait
- TH-86SQ2H 700cd/m² 24.7 Operation USB Media Player Portrait
- TH-75SQ2H 700cd/m² 24.7 Operation USB Media Player Portrait
- TH-65SQ2H 700cd/m² 24.7 Operation USB Media Player Portrait
- TH-55SQ2H 700cd/m² 24.7 Operation USB Media Player Portrait
- TH-50SQ2H 700cd/m² 24.7 Operation USB Media Player Portrait
- TH-43SQ2H 700cd/m² 24.7 Operation USB Media Player Portrait

SQE2



*Actual Resolution:
3840 x 2160p

• DisplayPort(Ver. 1.2)

*1: Some functions are limited.

AAG *only applies for 43-65"

- TH-98SQE2 500cd/m² 24.7 Operation USB Media Player Portrait
- TH-86SQE2 500cd/m² 24.7 Operation USB Media Player Portrait
- TH-75SQE2 500cd/m² 24.7 Operation USB Media Player Portrait
- TH-65SQE2 500cd/m² 24.7 Operation USB Media Player Portrait
- TH-55SQE2 500cd/m² 24.7 Operation USB Media Player Portrait
- TH-50SQE2 500cd/m² 24.7 Operation USB Media Player Portrait
- TH-43SQE2 500cd/m² 24.7 Operation USB Media Player Portrait

EQ2



*Actual Resolution:
3840 x 2160p

AAG *only applies for 43-65"

- TH-86EQ2 500cd/m² 18h Operation USB Media Player Portrait
- TH-75EQ2 500cd/m² 18h Operation USB Media Player Portrait
- TH-65EQ2 500cd/m² 18h Operation USB Media Player Portrait
- TH-55EQ2 500cd/m² 18h Operation USB Media Player Portrait
- TH-50EQ2 500cd/m² 18h Operation USB Media Player Portrait
- TH-43EQ2 500cd/m² 18h Operation USB Media Player Portrait

Entry

CQE2



*Actual Resolution:
3840 x 2160p

AAG *only applies for 43-65"

- TH-98CQE2 500cd/m² 24.7 Operation USB Media Player Portrait
- TH-86CQE2 400cd/m² 16h Operation USB Media Player Portrait
- TH-75CQE2 400cd/m² 16h Operation USB Media Player Portrait
- TH-65CQE2 500cd/m² 16h Operation USB Media Player Portrait
- TH-55CQE2 500cd/m² 16h Operation USB Media Player Portrait
- TH-50CQE2 500cd/m² 16h Operation USB Media Player Portrait
- TH-43CQE2 500cd/m² 16h Operation USB Media Player Portrait

Multi-Touch Screen

CQE2-IR



*Actual Resolution:
3840 x 2160p

- TH-86CQE2-IR 400cd/m² 16h Operation USB Media Player Portrait
- TH-75CQE2-IR 400cd/m² 16h Operation USB Media Player Portrait
- TH-65CQE2-IR 500cd/m² 16h Operation USB Media Player Portrait
- TH-55CQE2-IR 500cd/m² 16h Operation USB Media Player Portrait

Video Wall

VF2H/ VF2

- TH-55VF2H 700cd/m² 24.7 Operation DIGITAL LINK (HDMI CEC CONTROL) Portrait 0.88mm
- DisplayPort(Ver. 1.2)
- AAG Haze 28%

- TH-55VF2 500cd/m² 24.7 Operation DIGITAL LINK (HDMI CEC CONTROL) Portrait 0.88mm
- DisplayPort(Ver. 1.2)
- AAG Haze 28%

LFV9



- TH-55LFV9 500cd/m² 24.7 Operation USB Media Player Portrait 3.5mm
- DisplayPort(Ver. 1.2)
- AAG Haze 28%

Presentation and collaboration solution

WIRELESS PRESENTATION SYSTEM

For projector and displays

PressIT



For displays with SDM slot

WOLFVISION CYNAP PURE



CONFERENCE SOLUTION

PressIT360

TY-CSP1



Pitch for wall hanging is VESA compliant

NOTE: The specifications are subject to change without notice.

* The availability varies depending on model.

PressIT

Plug & Play Wireless Presentation System

Dongle based wireless presentation system for fast and simple screen sharing

Lineup



	Basic Set		Receiver (Board)	Transmitter (HDMI/USB)		Transmitter (USB Type-C)	
Model	TY-WPS1	TY-WPSC1	TY-SB01WP	TY-WP2B1	TY-WPB1	TY-WP2BC1	TY-WPBC1
Applicable product	Flat Panel Display / Projector (Panasonic and others)		SQ1/H, SQE2 and EQ2 series	PC/Tablet/Smartphone			
What's included?	1 Receiver (Box) x1 3 Transmitter (HDMI/USB) x2 5 Case for Transmitter x1	1 Receiver (Box) x1 4 Transmitter (USB Type-C) x2 5 Case for Transmitter x1	2 Receiver (Intel® SDM specification) x1	3 Transmitter (HDMI/USB) x2 5 Case for Transmitter x1	3 Transmitter (HDMI/USB) x1	4 Transmitter (USB Type-C) x2 5 Case for Transmitter x1	4 Transmitter (USB Type-C) x1



Connects to any devices*

HDMI-CEC command compatible

Low latency

Antibacterial surface treatment

Presents 4 screens in full HD (supports 4K)**

Lock mode prevents interruptions

Touch back function when used with a interactive display

Seamless video playback with zero lag

* Easy screen sharing with a dedicated app (IOS and Android)
** up to 32 transmitters at once

PressIT360

Providing a more realistic meeting with the 360-degree camera speakerphone



Certified for Microsoft Teams



High-quality images from a high-performance 360-degree camera
Four high-performance cameras provide 360-degree immersive images.

360-degree orientation microphone and speaker
Covers a 360-degree radius up to 5m/16.4ft for clear sound collection.

Easy to carry and operate meeting
Video and audio data can be sent to your PC with a single USB-C. Diameter 64 mm, height 285 mm, weight approx. 950 g.