

Product datasheet

Specifications



APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord

AP9565

Overview

Presentation

Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (12)C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.

Lead time

Main

Main Input Voltage	200 V 208 V 230 V
PDU type	Basic
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	1U
Cable length	2.50 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

Physical

Colour	Black
Height	4.4 cm
Width	44.7 cm
Depth	5.7 cm
Net weight	2.05 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Horizontal

Input

Input current limits	16 A
----------------------	------

Load capacity	3680 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	12 IEC 60320 C13
--------------------------------	------------------

Conformance

Product certifications	cUL listed CE Queensland Australia UL listed VDE
Standards	UL 60950

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	46.4 cm
Package 1 Length	22.9 cm
Package 1 Weight	3.632 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)