



Holder with key-lock

Active holder with cig-plug and tilt swivel. With Easy-switching system. Charging via pogo pins. Fits for device with original boot with/without handstrap. 3A charging. 12/24V. 2 keys included.

Item no: 735306

EAN Number: 7320287353068

This holder is the perfect choice when you want to secure your device and still have it easy accessible, while getting the battery charged. Customed with a perfect fit for device with original boot, with or without handstrap. The holder has an extra robust design for an extra secure fit, and is equipped with a lock. In order to remove the device from the holder you need a key (two keys are included). Easy one-hand insertion and removal. You have full access to the camera and all buttons and outlets when the device is in the holder.

With power supply, charging via pogo pin connection. With cig-plug cable that connects to the vehicle's 12/24 Volt socket. 3A charger.

Easy-switching system:

The easy-switching system enables you to upgrade the holder only, and keep the installed cables. It saves you a lot of time when upgrading to a new device, or for maintenance in case of warranty or damage. You simply disconnect the holder from the charging cable via the Molex 6-pin quick connector, and then connect the new holder. The switch is done in a few seconds.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade ABS/Acetal plastic. Color: black. Made in Sweden. Attach the holder to any flat surface or a Pedestal Mount in a truck, distribution vehicle, warehouse etc.

Fits the following models:

Zebra TC53
Zebra TC53e
Zebra TC58
Zebra TC58e

For a complete list, see

www.brodit.com/en/product/735306

Measurements:

Height 216 mm
Width 92 mm
Depth 70 mm
Volume 1391 cm³
Weight 310 g

Charging specifications:

Input voltage: DC/10-24V
Charging voltage: DC/4.6-5.3V
Output current(Typ): 3.0A
Input & output protection: Input polarity reversal/Output over voltage/Output over current/Output short protection
LED charging indicator: Product output indicator
Operating temperature: 0°C ~ +40°C
Storage temperature: -20°C ~ +80°C
RoHS compliant: ROHS