

Overview

HPE Aruba Networking 500H Series Unified Hospitality Access Points

High-performance and cost-effective Wi-Fi 6 (802.11ax) for hospitality, branch, and teleworker deployments

These economical Wi-Fi 6 access points provide high-performance connectivity for any organization experiencing growing mobile, cloud and IoT requirements. With a wireless aggregate data rate of up 1.5 Gbps and gigabit local wired ports, they deliver the range of connectivity options needed for venues such as hotels, residence halls, and remote offices alike.



HPE Aruba Networking 500H Series Unified Hospitality Access Points

Standard Features

Key Features

- Combine wireless and wired access in a single compact form-factor
 - Up to 1.5 Gbps of maximum wireless throughput
 - Up to 4 wired network ports and 1 Smart Rate uplink port
 - WPA3 and Enhanced Open security
 - Built-in technology that resolves sticky client issues for Wi-Fi 6 and Wi-Fi 5 devices
 - OFDMA and MU-MIMO for enhanced multi-user efficiency
 - IoT-ready Bluetooth 5 and Zigbee support
-

Incredible Efficiency

The HPE Aruba Networking 500H Series Unified Hospitality Access Points are designed to optimize user experience by maximizing Wi-Fi efficiency and dramatically reducing airtime contention between clients.

Features include Orthogonal frequency-division multiple access (OFDMA), multi-user MIMO and cellular optimization. With up to 4 spatial streams (4SS) and 80MHz channel bandwidth, the HPE Aruba Networking 500H Series provides groundbreaking wireless capabilities for budget-conscious deployments.

Read [the Multi-User 802.11ax white paper](#) for further information.

Advantages of OFDMA

This capability allows HPE Aruba Networking's APs to handle multiple Wi-Fi 6 capable clients on each channel simultaneously, regardless of device or traffic type. Channel utilization is optimized by handling each transaction via smaller sub-carriers or resource units (RUs), which means that clients are sharing a channel and not competing for airtime and bandwidth.

Aruba Air Slice for Extended OFDMA Assurance

APs in controller-less mode (Instant) can provide SLA-grade performance by allocating RUs to specific traffic types. By combining HPE Aruba Networking's Policy Enforcement Firewall (PEF) and Layer 7 deep packet inspection (DPI) to identify user roles and applications, the APs will dynamically allocate the bandwidth needed. Non-Wi-Fi 6 clients can also benefit. Air Slice for APs in controller mode will be supported in a future software release. Learn more in the technical brief.

Multi-user MIMO (MU-MIMO)

Similar to downlink MU-MIMO in Wi-Fi 5 (802.11ac Wave 2), the HPE Aruba Networking 500H Series Unified Hospitality Access Points can simultaneously connect clients using downlink – and now – uplink spatial streams. The added benefit is the ability to multiply the number of clients that can now send traffic, thus optimizing client-to-AP spatial stream diversity.

Wi-Fi 6 and MU-MIMO aware client optimization

HPE Aruba Networking's patented AI-powered ClientMatch technology eliminates sticky client issues by placing Wi-Fi 6 capable devices on the best available AP. Session metrics are used to steer mobile devices to the best AP based on available bandwidth, types of applications being used and traffic type – even as users roam.

Advanced Cellular Coexistence (ACC)

This feature uses built-in filtering to automatically minimize the impact of interference from cellular networks, distributed antenna systems (DAS), and commercial small cell or femtocell equipment.

Intelligent Power Monitoring (IPM)

HPE Aruba Networking APs continuously monitor and report hardware energy consumption. They can also be configured to enable or disable capabilities based on available PoE power – ideal when wired switches have exhausted their power budget.

Green AP energy efficiency

HPE Aruba Networking Wi-Fi 6 APs can use analytics from HPE Aruba Networking Central to automatically transition in and out of a sleep mode based on client density.



Standard Features

IoT Platform Capabilities

Like all HPE Aruba Networking Wi-Fi 6 APs, the HPE Aruba Networking 500H Series includes an integrated Bluetooth 5 and 802.15.4 radio (for Zigbee support) to simplify deploying and managing IoT-based location services, asset tracking services, security solutions and IoT sensors. This allows organizations to leverage the HPE Aruba Networking 500H Series as an IoT platform, which eliminates the need for an overlay infrastructure and additional IT resources.

Target Wake Time (TWT)

Ideal for IoTs that communicate infrequently, TWT establishes a schedule for when clients need to communicate with an AP. This helps improve client power savings and reduces airtime contention with other clients.

Advanced IoT Coexistence (AIC)

This feature uses built-in filtering to automatically minimize the impact of interference from IoT wireless radios like Bluetooth and Zigbee.

HPE Aruba Networking Secure Infrastructure

The HPE Aruba Networking 500H Series Unified Hospitality Access Points includes components of HPE Aruba Networking's 360 Secure Fabric to help protect user authentication and wireless traffic.

WPA3 and Enhanced Open

Support for stronger encryption and authentication is provided via the latest version of WPA for enterprise protected networks. Enhanced Open offers seamless new protection for users connecting to open networks where each session is automatically encrypted to protect user passwords and data on guest networks.

WPA2-MPSK

MPSK enables simpler passkey management for WPA2 devices – should the Wi-Fi password on one device or device type change, no additional changes are needed for other devices. This requires ClearPass Policy Manager.

VPN Tunnels

In Remote AP (RAP) and IAP-VPN deployments, the HPE Aruba Networking 500H Series can be used to establish a secure SSL/IPSec VPN tunnel to a Mobility Controller that is acting as a VPN concentrator.

Trusted Platform Module (TPM)

For enhanced device assurance, all HPE Aruba Networking APs have an installed TPM for secure storage of credentials, keys, and boot code.

Simple and Secure Access

To simplify policy enforcement, the HPE Aruba Networking 500H Series uses HPE Aruba Networking's Policy Enforcement Firewall (PEF) to encapsulate all traffic from the AP to the mobility controller (or gateway) for end-to-end encryption and inspection. Policies are applied based on user role, device type, applications, and location. This reduces the manual configuration of SSIDs, VLANs and ACLs. PEF also serves as the underlying technology for dynamic segmentation.

High-Density Connectivity

Each HPE Aruba Networking 500H Series AP provides connectivity for a maximum of 256 associated clients per radio (512 in total). In real-world scenarios, the maximum recommended client density is dependent on environmental conditions.

Versatile Installation Options

The APs can be deployed as a wall-mount or, for remote teleworker environments, they can be converted to a desk-mount by using an optional accessory stand.

Flexible Operation and Management

A unique feature of HPE Aruba Networking APs is the ability to operate in either controller-less (Instant) or controller-based mode.



Standard Features

Controller-less (Instant) mode

In controller-less mode, one AP serves as a virtual controller for the entire network. Learn more about Instant mode in [this technology brief](#).

Mobility Controller mode

For optimized network performance, roaming and security, APs tunnel all traffic to a mobility controller for centrally managed traffic forwarding and segmentation, data encryption, and policy enforcement. Learn more in the HPE Aruba Networking OS datasheet.

Management options

Available management solutions include HPE Aruba Networking Central (cloud-managed) or Aruba AirWave – a multi-vendor on-premises management solution.

For large installations across multiple sites, APs can be factory-shipped and can be activated with Zero Touch Provisioning through HPE Aruba Networking Central or AirWave. This reduces deployment time, centralizes configuration, and helps manage inventory.

HPE Aruba Networking 500H Remote AP bundles

To simplify the ordering and distribution of HPE Aruba Networking 500H Series Unified Hospitality Access Points, we offer a number of AP bundles that combine an AP variant a desk stand, power adapter, and North American or European power cord. This makes it easier to get remote workers and small branches up and running quickly.

Additional Wi-Fi Features

Each AP also includes the following standards-based technologies:

- Advanced Cellular Coexistence (ACC) minimizes the impact of interference from cellular networks
 - Advanced IOT Coexistence (AIC) allows concurrent operation of multiple radios in the 2.4GHz band
 - Maximum ratio combining (MRC) for improved receiver performance
 - Cyclic delay/shift diversity (CDD/CSD) for improved downlink RF performance
 - Space-time block coding (STBC) for increased range and improved reception
 - Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
 - Transmit beam-forming (TxBF) for increased signal reliability and range
 - 802.11ax Target Wait Time (TWT) to support low-power client devices
-



Configuration Information

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

BTO Models

Remarks	Description	SKU
	Aruba AP-503H	
Notes:	Add Mount Kit (not included)	
	Aruba AP-503H (EG) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V44A
	Aruba AP-503H (IL) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V42A
	Aruba AP-503H (JP) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V40A
	Aruba AP-503H (RW) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V36A
	Aruba AP-503H (US) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V38A
	Aruba AP-503HR	
Notes:	Bundle includes Mount Kit, Power Supply and Power Cord	
	Aruba AP-503HR (EU) Remote AP bundle with AP-503H (RW) + desk mount + power adapter + EU power cord	R7G96A
	Aruba AP-503HR (US) Remote AP bundle with AP-503H (US) + desk mount + power adapter + NA power cord	R7G97A
	Aruba AP-505H	
Notes:	Add Mount Kit (not included)	
	Aruba AP-505H (EG) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V54A
	Aruba AP-505H (IL) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V52A
	Aruba AP-505H (JP) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V50A
	Aruba AP-505H (RW) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V46A
	Aruba AP-505H (US) Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V48A
	Aruba AP-505HR	
Notes:	Bundle includes Mount Kit, Power Supply and EU Power Cord	
	Aruba AP-505HR (EU) Remote AP bundle with AP-505H (RW) + desk mount + power adapter + EU power cord	R3V56A
Notes:	Bundle includes Mount Kit, Power Supply and US Power Cord	
	Aruba AP-505HR (US) Remote AP bundle with AP-505H (US) + desk mount + power adapter + NA power cord	R3V57A
	Aruba AP-503H TAA	
Notes:	Add Mount Kit (not included)	
	Aruba AP-503H (EG) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V45A
	Aruba AP-503H (IL) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V43A
	Aruba AP-503H (JP) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V41A
	Aruba AP-503H (RW) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V37A
	Aruba AP-503H (US) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+2 Ethernet	R3V39A
	Aruba AP-505H TAA	
Notes:	Add Mount Kit (not included)	
	Aruba AP-505H (EG) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V55A
	Aruba AP-505H (IL) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V53A
	Aruba AP-505H (JP) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V51A
	Aruba AP-505H (RW) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V47A
	Aruba AP-505H (US) TAA Dual-radio 802.11ax 2x2 Unified Hospitality AP with 1+4 Ethernet PSE USB	R3V49A
Notes:	OCA Only Model Selection Form -> HPE Aruba Networking > Wireless > Access Points > Hospitality / Remote:>HPE Aruba Networking 500H Series Unified Hospitality Access Points	



Configuration Information

Mount Accessories

Aruba AP-Mount Kits

1, 2, 3	AP-500H-MNT1 Kit with Single-gang Wall-box Mount Adapter for 500H Series AP	R3V58A
Notes:	For wall and (wiring) wall-box	
1, 3	AP-505H-MNT2 Kit with Dual-gang Wall-box Mount Adapter for AP-505H	R3V59A
Notes:	For wall and (wiring) wall-box	
2, 3	AP-500H-MNTD Kit with Desk Mount Adapter for 500H Series AP	R3V60A
Notes:	For desk	
1, 2, 3	AP-503H-MNT2 Kit with Dual-gang Wall-box Mount Adapter for AP-503H	R3V61A
Notes:	For wall and (wiring) wall-box	
1, 2, 3	HPE Aruba Networking AP-500H-MNTD2 RJ45 Ethernet Jack Desk Mount	S0J41A
Notes:	For desk	

Configuration Rules

Rule#	Description	SKU
1	For HPE Aruba Networking 503H Series Std (Min 0 // max 1) User Selection (min 1 // max 1)	
2	For HPE Aruba Networking 505H Series Std (Min 0 // max 1) User Selection (min 1 // max 1)	
3	For HPE Aruba Networking 503HR/505HR Series Std (Min 0 // max 0) User Selection (min 0 // max 0)	

Power Options

Rule #	Description	SKU
	Power Options	
Notes:	Most devices are PoE powered from switch so these are optional	
1, 2, 4	AP-AC2-12B 12V/48W AC/DC desktop style power adapter with 2.1/5.5mm connector <ul style="list-style-type: none"> Add AC power cord, Unrestricted 	R3K00A
1, 3, 4	AP-AC2-48C 48V/50W AC/DC desktop style power adapter with 1.35/3.5mm connector <ul style="list-style-type: none"> Add AC power cord, Unrestricted 	R3K01A
1, 2, 3, 4	AP-POE-AFGE 1-Port GbE 802.3af 15.4W midspan injector <ul style="list-style-type: none"> Add AC Power Cord, Unrestricted(AP-503H) 	R6P68A
1, 3, 4	AP-POE-ATSR 1-Port Smart Rate 802.3at 30W midspan injector	R6P67A
1, 3, 4	AP-POE-BTSR 1-Port Smart Rate 802.3bt 60W midspan injector <ul style="list-style-type: none"> Add AC power cord, Unrestricted 	R1C73A

Configuration Rules

Rule#	Description	SKU
1	If this Power Supply is selected, bring in (Min 1 // Max 1) Localized power cord based on the HPE Aruba Networking Localization Menu	
2	For HPE Aruba Networking 503H Series Std (Min 0 // max 1) User Selection (min 0 // max 1)	
3	For HPE Aruba Networking 505H Series Std (Min 0 // max 1) User Selection (min 0 // max 1)	
4	For 503HR/505HR Series Std (Min 0 // max 0) User Selection (min 0 // max 0)	

Accessories

Other Accessories

For HPE Aruba Networking 503H/505H Series Std (Min 0 // max 99) User Selection (min 0 // max 99)	
For HPE Aruba Networking 503HR/505HR Series Std (Min 0 // max 99) User Selection (min 0 // max 99)	
AP-CBL-SERU Micro-USB TTL3.3V to USB2.0 AP Console Adapter Cable	JY728A
AP-MOD-SERU Micro-USB TTL3.3V to RJ45 RS232 AP Console Adapter Module	R6Q99A



Configuration Information

Aruba AP-MC-SFP Media Converter Module for WLAN Access Points (SFP with DC to Copper with POE)	R8F89A
Aruba USB LTE Modem for use with Access Points and Gateways	R8F34A
Aruba USB Extender Cable Kit for use with Aruba USB LTE Modem	R8G76A

Notes: [Drivers available on the HPE Aruba Networking Support Center](#)

Software

Central

Cloud Services / Access Point Foundation Subscriptions

2, 8	HPE Aruba Networking Central AP Foundation 1 year Subscription E-STU	Q9Y58AAE
2, 8	HPE Aruba Networking Central AP Foundation 3 year Subscription E-STU	Q9Y59AAE
2, 8	HPE Aruba Networking Central AP Foundation 5 year Subscription E-STU	Q9Y60AAE
2, 8	HPE Aruba Networking Central AP Foundation 7 year Subscription E-STU	Q9Y61AAE
2, 8	HPE Aruba Networking Central AP Foundation 10 year Subscription E-STU	Q9Y62AAE

Cloud Services / Access Point Advanced Subscriptions

2, 8	HPE Aruba Networking Central AP Advanced 1 year Subscription E-STU	Q9Y63AAE
2, 8	HPE Aruba Networking Central AP Advanced 3 year Subscription E-STU	Q9Y64AAE
2, 8	HPE Aruba Networking Central AP Advanced 5 year Subscription E-STU	Q9Y65AAE
2, 8	HPE Aruba Networking Central AP Advanced 7 year Subscription E-STU	Q9Y66AAE
2, 8	HPE Aruba Networking Central AP Advanced 10 year Subscription E-STU	Q9Y67AAE

On-Prem Services / Access Point Foundation Subscriptions

3, 8	HPE Aruba Networking Central on Prem AP Foundation 1 year Subscription E-STU	R6U63AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 3 year Subscription E-STU	R6U64AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 5 year Subscription E-STU	R6U65AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 7 year Subscription E-STU	R6U66AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 10 year Subscription E-STU	R6U67AAE

FedRAMP Services / Access Point Advanced Subscriptions

6, 8	Aruba Central AP Advanced 1yr Subscription Government E-STU	R8K84AAE
6, 8	Aruba Central AP Advanced 3yr Subscription Government E-STU	R8K85AAE
6, 8	Aruba Central AP Advanced 5yr Subscription Government E-STU	R8K86AAE
6, 8	Aruba Central AP Advanced 7yr Subscription Government E-STU	R8K87AAE
6, 8	Aruba Central AP Advanced 10yr Subscription Government E-STU	R8K88AAE

Configuration Rules

Rule #	Description	SKU
2	Add the Central Cloud Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking > Network Management > Central > Cloud Services	
3	Add the Central On-Prem Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking > Network Management > Central > On-Prem Services	
6	Add the Central FedRAMP Service Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking > Network Management > Central > FedRAMP	
8	For OCA: When configuring the following AP 10-Pack, selection condition for this Subscription should be 0(default) or 10	
	HPE Aruba Networking AP-503 (RW) Dual Radio 2x2 802.11ax Wi-Fi 6 10-pack Campus Access Point	S1E83A
	HPE Aruba Networking AP-503 (US) Dual Radio 2x2 802.11ax Wi-Fi 6 10-pack Campus Access Point	S1E84A



Configuration Information

As-a-Service

Cloud Services / Access Point Foundation Subscriptions

7	HPE Aruba Networking Central AP Foundation 1 year Subscription SaaS	Q9Y58AAS
7	HPE Aruba Networking Central AP Foundation 3 year Subscription SaaS	Q9Y59AAS
7	HPE Aruba Networking Central AP Foundation 5 year Subscription SaaS	Q9Y60AAS
7	HPE Aruba Networking Central AP Foundation 7 year Subscription SaaS	Q9Y61AAS
7	HPE Aruba Networking Central AP Foundation 10 year Subscription SaaS	Q9Y62AAS

Cloud Services / Access Point Advanced Subscriptions

7	HPE Aruba Networking Central AP Advanced 1 year Subscription SaaS	Q9Y63AAS
7	HPE Aruba Networking Central AP Advanced 3 year Subscription SaaS	Q9Y64AAS
7	HPE Aruba Networking Central AP Advanced 5 year Subscription SaaS	Q9Y65AAS
7	HPE Aruba Networking Central AP Advanced 7 year Subscription SaaS	Q9Y66AAS
7	HPE Aruba Networking Central AP Advanced 10 year Subscription SaaS	Q9Y67AAS

Configuration Rules

Rule#	Description	SKU
7	For IRIS reference only. No action required for OCX and Clic	



Technical Specifications

Hardware Variants

- HPE Aruba Networking AP-503H:
Mid-range dual radio Wi-Fi 6 Hospitality AP with 1+2 Ethernet ports
- HPE Aruba Networking AP-505H:
High-end dual radio Wi-Fi 6 Hospitality AP with 1+4 Ethernet ports, PSE, USB

Dimensions and weight

HPE Aruba Networking AP-503H

- Unit by itself:
 - 86mm (W) x 47mm (D) x 150mm (H)
 - 360g
- Unit in shipping box:
 - 111mm (W) x 54mm (D) x 167mm (H)
 - 450g

HPE Aruba Networking AP-505H

- Unit by itself:
 - 86 (W) x 47 (D) x 150 mm (H) / 3.4 (W) x 1.9 (D) x 5.9 in (H)
 - 360 gm / 0.8 lb
- Unit in shipping box:
 - 111 (W) x 54 (D) x 167 mm (H) / 4.4 (W) x 2.1 (D) x 6.6 in (H)
 - 450 gm / 1.0 lb

Wi-Fi Antennas

- HPE Aruba Networking AP-503H:
 - Two integrated semi-directional antennas for 2x2 MIMO with peak single antenna gain of 5.2dBi in 2.4GHz and 5.4dBi in 5GHz. Built-in antennas are optimized for vertical wall or desk mounted orientation of the AP.
 - Combining the patterns of each of the antennas of the MIMO radios, the peak gain of the combined, average pattern is 1.7dBi in 2.4GHz and 5.0dBi in 5GHz.
- HPE Aruba Networking AP-505H:
 - Two integrated semi-directional antennas for 2x2 MIMO with peak antenna gain of 6.3dBi in 2.4GHz and 5.4dBi in 5GHz. Built-in antennas are optimized for vertical wall or desk mounted orientation of the AP.
 - Combining the patterns of each of the antennas of the MIMO radios, the peak gain of the combined, average pattern is 3.3dBi in 2.4GHz and 2.9dBi in 5GHz.

Crypto Performance

- HPE Aruba Networking AP-503H:
VPN IPsec throughput performance: 100Mbps or better
- HPE Aruba Networking AP-505H:
VPN IPsec throughput performance: 500Mbps or better.

Regulatory Model Numbers

- HPE Aruba Networking AP-503H (all variants)
APINH503
- HPE Aruba Networking AP-505H (all variants)
APINH505

Mounting

- Optional mounting kits: Using one of the (separate orderable) mount kits, the AP can be attached to a single or dual gang wall-box, directly to a wall, or desk mounted. See the HPE Aruba Networking 500H Series Ordering Guide for details.



Technical Specifications

WI-FI Radio Specifications

5 GHz

- Two spatial stream (SU/MU) MIMO for up to 1.2Gbps wireless data rate

2.4 GHz

- Two spatial stream (SU/MU) MIMO for up to 287Mbps wireless data rate
Notes: HE40 operation is supported in 2.4GHz, but uncommon and not recommended for enterprise deployments
- Support for up to 256 associated client devices per radio, and up to 16 BSSIDs per radio
- Supported frequency bands (country-specific restrictions apply):
- 2.400 to 2.500GHz (ISM), channels 1-13
 - 5.150 to 5.250GHz (U-NII-1), channels 36, 40, 44, 48
 - 5.250 to 5.350GHz (U-NII-2A), channels 52, 56, 60, 64
 - 5.470 to 5.725GHz (U-NII-2C), channels 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144
 - 5.725 to 5.850GHz (U-NII-3), channels 149, 153, 157, 161, 165
 - 5.850 to 5.925GHz (U-NII-4), channels 169, 173, 177
- Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
- Supported radio technologies:
 - 802.11b: Direct-sequence spread-spectrum (DSSS)
 - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
- 802.11ax: Orthogonal frequency-division multiple access (OFDMA) with up to 8 resource units (RU)
- Supported modulation types:
 - 802.11b: BPSK, QPSK, CCK
 - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM (proprietary extension)
 - 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024 QAM (proprietary extension)
 - 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024 QAM
- 802.11n high-throughput (HT) support: HT 20/40
- 802.11ac very high throughput (VHT) support: VHT 20/40/80
- 802.11ax high efficiency (HE) support: HE20/40/80
- Supported data rates (Mbps):
 - 802.11b: 1, 2, 5.5, 11
 - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
 - 802.11n: 6.5 to 300 (MCS0 to MCS15, HT20 to HT40), 400 with 256-QAM
 - 802.11ac: 6.5 to 867 (MCS0 to MCS9, NSS = 1 to 2 for VHT20 to VHT160), 1,083 with 1024-QAM
 - 802.11ax (2.4GHz): 3.6 to 574 (MCS0 to MCS11, NSS = 1 to 2, HE20 to HE40)
 - 802.11ax (5GHz): 3.6 to 1,201 (MCS0 to MCS11, NSS = 1 to 4, HE20 to HE80)
- 802.11n/ac packet aggregation: A-MPDU, A-MSDU
- Transmit power: Configurable in increments of 0.5 dBm
- Maximum (aggregated, conducted total) transmit power (limited by local regulatory requirements):
 - 2.4 GHz band: +21 dBm (18 dBm per chain)
 - 5 GHz band: +21 dBm (18 dBm per chain)**Notes: conducted transmit power levels exclude antenna gain**
- Minimum configurable transmit power level: 0dBm (conducted, per chain)

Certifications

- Wi-Fi Alliance:
 - Wi-Fi CERTIFIED™ a, b, g, n, ac
 - Wi-Fi CERTIFIED™ 6 (ax)
 - WPA, WPA2 and WPA3 – Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)
 - WMM, WMM-PS, Wi-Fi Vantage, Wi-Fi Agile Multiband
 - Passpoint (release 2)
- Bluetooth SIG (HPE Aruba Networking AP-505H only)
- Ethernet Alliance (POE, PD device, class 6)

Technical Specifications

Additional interfaces

- HPE Aruba Networking AP-503H:
 - Uplink (E0): Ethernet wired network port (RJ45)
 - Auto-sensing link speed (10/100/1000BASE-T) and MDI/MDX
 - 802.3az Energy Efficient Ethernet (EEE)
 - POE-PD: 802.3af POE (class 3)
 - Local (E1-E2): Two Ethernet wired network ports (RJ45)
 - Auto-sensing link speed (10/100/1000BASE-T) and MDI/MDX
 - 802.3az Energy Efficient Ethernet (EEE)
 - DC power interface: 12Vdc (nominal, +/- 5%), accepts 2.1mm/5.5mm center-positive circular plug with 9.5mm length
- HPE Aruba Networking AP-505H:
 - E0: HPE SmartRate port (RJ-45)
 - Auto-sensing link speed (100/1000/2500BASE-T) and MDI/MDX
 - 2.5Gbps speed complies with NBase-T and 802.3bz specifications
 - 802.3az Energy Efficient Ethernet (EEE)
 - E1-4: 10/100/1000BASE-T (RJ-45)
 - Auto-sensing link speed and MDI/MDX
 - 802.3az Energy Efficient Ethernet (EEE)
 - E1-2: POE-PSE, 48Vdc (nominal) 802.3af/at POE output (max 30W combined)
 - DC power interface: 48Vdc (nominal, +/- 5%), accepts 1.35mm/3.5mm center-positive circular plug with 9.5mm length
- Bluetooth Low Energy (BLE5.0) and Zigbee (802.15.4) radio
 - BLE: up to 7dBm transmit power (class 1) and -100dBm receive sensitivity (125kbps)
 - Zigbee: up to 7dBm transmit power and -98dBm receive sensitivity (250kbps)
 - Integrated semi-directional antenna with peak gain of 1.2dBi
- USB 2.0 (Type A):
 - Cellular modems
 - IOT or other plug-in accessories
 - Device battery charging port
 - Capable of sourcing up to 1A / 5W to an attached device
- Visual indicators (2 multi-color LEDs):
 - Power/System status
 - Radio status
 - Local network port status (4x)
 - POE-PSE status (2x)
- Serial console interface: proprietary, micro-B USB physical jack
- Security slot: Kensington security slot

Regulatory

- FCC/ISED
- CE Marked
- RED Directive 2014/53/EU
- EMC Directive 2014/30/EU
- Low Voltage Directive 2014/35/EU
- IEC/EN 60950
- EN 60601-1-1, EN60601-1-2
- IEC/EN 62368-1

For more country-specific regulatory information and approvals, please see your HPE Aruba Networking representative.



Technical Specifications

Power

- Supports direct DC power and Power over Ethernet (PoE)
- When both DC and PoE power sources are available, DC power takes priority over PoE
- Power sources are sold separately; see the HPE Aruba Networking 500H Series Ordering Guide for details
- HPE Aruba Networking AP-503H:
 - When powered by DC or 802.3af (class 3) POE, the AP will operate without restrictions.
 - Maximum (worst-case) power consumption:
 - DC powered: 14W
 - POE powered (802.3af): 13.5W
 - Maximum (worst-case) power consumption in idle mode: 6.2W
 - Maximum (worst-case) power consumption in deep-sleep mode: 3.5W
- HPE Aruba Networking AP-505H:
 - When powered by DC or 802.3bt (class 6) PoE, the AP will operate without restrictions.
 - When powered by 802.3at (class 4) PoE and with the IPM feature disabled, the AP will disable the USB port (only) if PoE-PSE is enabled and limit PoE-PSE power to 12.5W. In the same configuration but with IPM enabled, the AP will (only) limit PoE-PSE power to 15.4W (802.3af class 3), but may dynamically apply additional restrictions depending on the PoE budget and actual power. The feature restrictions and order can be programmed.
 - Maximum (worst-case) power consumption (without USB or PSE / max):
 - DC powered: 12W / 50W
 - PoE powered (802.3bt): 12W / 50W
 - PoE powered (802.3at): 12W / 25.5W
 - PoE powered (802.3af): 12W / 13.5W
 - Maximum (worst-case) power consumption in idle mode: 6W (DC) or 6W (PoE)
 - Maximum (worst-case) power consumption in deep-sleep mode: 3W (DC) or 3W (PoE)

Environmental

- Operating:
 - Temperature: -0° C to +40° C (+32° F to +104° F)
 - Humidity: 5% to 93% non-condensing
 - ETS 300 019 class 3.2 environments
- Storage and transportation:
 - Temperature: -40° C to +70° C (-40° F to +158° F)
 - Humidity: 5% to 93% non-condensing
 - ETS 300 019 classes 1.2 and 2.3 environments

Warranty

- **Limited lifetime warranty**

Minimum Operating System Software

- HPE Aruba Networking OS and HPE Aruba Networking InstantOS 8.7.1.0 (HPE Aruba Networking AP-503H) and 8.7.0.0 (HPE Aruba Networking AP-505H)
-



Technical Specifications

RF Performance Table		
	Maximum transmit power (dBm) per transmit chain	Receiver sensitivity (dBm) per receive chain
2.4GHz, 802.11b		
1Mbps	18	-98
11Mbps	18	-90
2.4GHz, 802.11g		
6Mbps	18	-93
54Mbps	18	-76
2.4GHz, 802.11n HT20		
MCS0	18	-93
MCS7	16	-75
2.4GHz, 802.11ax HE20		
MCS0	18	-93
MCS11	14	-62
5GHz, 802.11a		
6Mbps	18	-92
54Mbps	18	-75
5GHz, 802.11n HT20		
MCS0	18	-92
MCS7	16	-74
5GHz, 802.11n HT40		
MCS0	18	-90
MCS7	16	-71
5GHz, 802.11ac VHT20		
MCS0	18	-90
MCS9	16	-69
5GHz, 802.11ac VHT40		
MCS0	18	-90
MCS9	16	-65
5GHz, 802.11ac VHT80		
MCS0	18	-87
MCS9	16	-62
5GHz, 802.11ax HE20		
MCS0	18	-93
MCS11	14	-62
5GHz, 802.11ax HE40		
MCS0	18	-90
MCS11	14	-59
5GHz, 802.11ax HE80		
MCS0	18	-87
MCS11	14	-56

Notes: Table shows the maximum capability of the hardware provided (excluding antenna gain). Maximum transmit power is limited by local regulatory settings.






Summary of Changes

Date	Version History	Action	Description of Change
04-Dec-2023	Version 12	Changed	Series name was updated.
07-Aug-2023	Version 11	Changed	Configuration Information section was updated.
06-Mar-2023	Version 10	Changed	Configuration Information section was updated.
21-Nov-2022	Version 9	Changed	Updates worked through out the document.
15-Aug-2022	Version 8	Changed	Configuration Information section was updated.
05-Jul-2022	Version 7	Changed	Configuration Information section was updated, new SKUs were added.
06-Dec-2021	Version 6	Changed	SKUs were added in Configuration Information section was updated.
15-Mar-2021	Version 5	Changed	Configuration Information section was updated.
01-Feb-2021	Version 4	Changed	Configuration Information section was updated.
04-Jan-2021	Version 3	Changed	Standard Features and Configuration Information sections were updated. New SKUS were added.
08-Sep-2020	Version 2	Changed	Configuration Information section was updated. New SKUS were added.
04-May-2020	Version 1	New	New QuickSpecs



Copyright

Make the right purchase decision.
Contact our presales specialists.



© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00056117enw - 16331 - Worldwide - V12 - 04-December-2023