

# Rittal – The System.

Faster – better – everywhere.

## FlatBox – DK 7507.030

Date : Dec 7, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# FlatBox – DK 7507.030

created: 07.12.2020 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Design:</b>	with 482.6 mm (19") mounting frame
<b>Description:</b>	For flexible use as a wall-mounted or floor-standing enclosure.
<b>Benefits:</b>	Tool-free quick assembly System assembly on the open 482.6 mm (19") frame
<b>Material:</b>	Sheet steel Viewing window: Single-pane safety glass, 3 mm
<b>Surface finish:</b>	Powder-coated
<b>Colour:</b>	RAL 7035
<b>Supply includes:</b>	Flat-packed enclosure 1 wall section 2 basic supports 2 roof/base plates, with cut-outs for cable entry via brush strips 2 side panels, lockable 1 glazed door, lockable, security lock 3524 E, door hinge point selectable Connection components for tool-free, fast assembly Earthing kit for system-compatible earthing of all enclosure parts 482.6 mm (19") mounting frame
<b>Note:</b>	Max. installation depth: Depth - 58 mm to rear panel Max. distance between two 482.6 mm (19") levels: Depth - 104 mm
<b>Basic material:</b>	Sheet steel

## Product features

<b>Dimensions:</b>	Width: 600 mm Height: 758 mm Depth: 400 mm
<b>Installation height for components:</b>	15 U
<b>Load capacity:</b>	max. 750 N
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	30 kg
<b>EAN:</b>	4028177551428
<b>Customs tariff number:</b>	94032080
<b>ETIM 7.0:</b>	EC002500
<b>ETIM 6.0:</b>	EC002500
<b>eCl@ss 8.0/8.1:</b>	27180208
<b>eCl@ss 6.0/6.1:</b>	27180208
<b>Product description:</b>	DK FlatBox, WHD: 600x758x400 mm, 15 U, with 482.6 mm (19") mounting frame
<b>Approvals</b>	
<b>Certificates:</b>	EAC