EcoTank ET-M3180



Print, scan, copy and fax with this EcoTank including 11,000 pages' worth of ink, a three-year warranty¹, and Ethernet, Wi-Fi and USB connectivity.

Mono EcoTank printer for business, with an extremely low TCO in a userfriendly, stylish and compact design. Print up to an amazing 11,000 pages with the included ink that comes in a bottle for mess-free, easy refills. Wi-Fi, USB and Ethernet connectivity, PCL support, and a fast FPOT of six seconds all help to keep productivity high.

Save money

A high ink yield combined with Epson's economical inkjet technology delivers a low TCO and a competitive cost per page.

Save time

This reliable cartridge-free printer features an enhanced ink filling system and easy-to use-ink bottles, keeping intervention to a minimum. Thanks to the ink tank being positioned at the front of the printer, with a clear view of the ink levels, this new design is compact and provides easy access for refilling. Its fast First Page Out Time (FPOT) of six seconds from sleep, and 20ppm print speed, mean you won't be waiting around for jobs.

Save energy

Unlike a laser, our inkjet technology doesn't need any heat during the printing process, helping to keep energy use low and reduce electricity bills.

Business features

Wi-Fi, Ethernet and USB connectivity and a compact footprint mean that it's easy to place on a desktop and connect to a user's PC or laptop.

DATASHEET / BROCHURE



KEY FEATURES

- Low TCO and energy use Keep your printing costs extremely low
- High ink yields Print up to 11,000 pages with the included ink
- Save time Print, scan, copy and fax
- Built for business Duplex printing and PCL support
- Easy connectivity Wi-Fi, USB and Ethernet



PRODUCT SPECIFICATIONS

TECHNOLOGY		
Printing Method	PrecisionCore™ TFP print head	
Nozzle Configuration	400 Nozzles Black 2,8 pl Pigment ink Home Office, Office Desktop, Office Workgroup Print, Scan, Copy, Fax	
Minimum Droplet Size		
Ink Technology		
Category		
All-in-One Functions		
PRINT		
First Page Out	Monochrome 6 Seconds	
Printing Speed ISO/IEC 2473	4 20 pages/min Monochrome	
Duplex Printing Speed 9 A4 Pages/min Monochrome		
ISO/IEC 24734		
Maximum Printing Speed	39 pages/min Monochrome (plain paper 75 g/m²)	
Printing Resolution	1.200 x 2.400 DPI	
Printing Volume	5.000 pages per month	
	The maximum number of printed pages per month based on the performance capabilities or	
	the printer, including ISO rated print speeds and paper handling capabilities.	
Recommended Duty Cycle	200 - 1.500 pages per month	
Colours	Black	
For detailed information on p	rinting speeds please visit http://www.epson.eu/testing.	
SCAN		
Scanning Speed	7 ipm (Monochrome, Simplex, 200 dpi, ADF); 7 ipm (Colour, Simplex, 200 dpi, ADF);	
Optical Resolution	1.200 DPI x 2.400 DPI (Horizontal x Vertical)	
Optical Resolution (ADF)	1.200 DPI x 2.400 DPI (Horizontal x Vertical)	
Output formats	BMP, JPEG, PICT, TIFF, multi-TIFF, PDF, PNG	
Output formats Scanner type	BMP, JPEG, PICT, TIFF, multi-TIFF, PDF, PNG Contact image sensor (CIS)	
Scanner type		
Scanner type	Contact image sensor (CIS)	
Scanner type FAX Type of fax	Contact image sensor (CIS) Walk-up black and white and colour fax capability	
Scanner type FAX Type of fax Fax Transmission Speed	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max)	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart)	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max)	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed Copy resolution (dpi)	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed Copy resolution (dpi) Reduction / Enlargement	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 %	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed Copy resolution (dpi) Reduction / Enlargement Maximum number of copies	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed Copy resolution (dpi) Reduction / Enlargement	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 %	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed Copy resolution (dpi) Reduction / Enlargement Maximum number of copies	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed Copy resolution (dpi) Reduction / Enlargement Maximum number of copies Maximum Copy Size	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy Speed Copy resolution (dpi) Reduction / Enlargement Maximum number of copies Maximum Copy Size CONNECTIVITY	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99 A4	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy resolution (dpi) Reduction / Enlargement Maximum number of copies Maximum Copy Size CONNECTIVITY Network Printing Protocols	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black "Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99 A4	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy resolution (dpi) Reduction / Enlargement Maximum number of copies Maximum Copy Size CONNECTIVITY Network Printing Protocols Network Management	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black "Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99 A4 IPP, LDP, Port 9100, WSD SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy resolution (dpi) Reduction / Enlargement Maximum number of copies Maximum Copy Size CONNECTIVITY Network Printing Protocols Network Management Protocols	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99 Ad IPP, LDP, Port 9100, WSD SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping WSD-Scan	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy resolution (dpi) Reduction / Enlargement Maximum number of copies Maximum Copy Size CONNECTIVITY Network Printing Protocols Network Scanning Protocols Network Scanning Protocols	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99 Ad IPP, LDP, Port 9100, WSD SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping WSD-Scan	
Scanner type FAX Type of fax Fax Transmission Speed Error correction mode Fax speed dials (max) Page memory Fax Functions COPY Copy resolution (dpi) Reduction / Enlargement Maximum number of copies Maximum Copy Size CONNECTIVITY Network Printing Protocols Network Scanning Protocols Network Scanning Protocols	Contact image sensor (CIS) Walk-up black and white and colour fax capability Up to 33.6kbps / Approx. 3 sec/page CCITU/ITU Group3 fax with Error Correction Mode 100 names and numbers Up to 180 pages (ITU-T No.1 chart) PC Fax, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception Up to 17 ipm Black *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735) 600 x 600 25 % - 400 % 99 A4 IPP, LDP, Port 9100, WSD SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping WSD-Scan Hi-Speed USB - compatible with USB 2.0 specification, Ethernet interface (100 Base-TX / 100	

EcoTank ET-M3180

WHAT'S IN THE BOX

- X2 ink bottles
- Warranty document
- Main unit
- Power cable



PRODUCT SPECIFICATIONS

PAPER / MEDIA HANDLING		
Paper Formats	A4 (21.0x29.7 cm), Legal, Letter, Executive, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B5	
	(17.6x25.7 cm), B6 (12.5x17.6 cm), C6 (Envelope), No. 10 (Envelope), DL (Envelope)	
Automatic Document Feed	35 pages	
Compatible Paper Weight	64 g/m² - 256 g/m²	
Duplex	Yes	
Output Tray Capacity	100 Sheets	
Paper Tray Capacity	250 Sheets Standard, 250 Sheets Maximum	
Standard paper tray(s)	250-sheet paper tray	
Maximum paper input	250	
Rear paper path (special	Yes	
media)		
Number of paper trays	1	
GENERAL		
Recommended number of	From: 1 To: 3	
users		
Energy Use	12 Watt (standalone copying, ISO/IEC 24712 pattern), 1 Watt (sleep mode), 5,7 Watt (Ready),	
	0,2 Watt (Power off), TEC 0,18 kWh/week	
Supply Voltage	AC 220 V - 240 V	
Product dimensions	375 x 347 x 346 mm (Width x Depth x Height)	
Product weight	7,3 kg	
Noise Level	6,9 B (A) according to ISO 7779 pattern with Epson Premium Glossy Photo Paper / Photo RPM mode - 56 dB (A) according to ISO 9296	
Compatible Operating	Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X	
Systems	10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit),	
	Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Serve	
	2003 SP2, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012	
	(64bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows	
	XP Professional x64 Edition SP2 or later, Windows XP SP3 or later (32-bit)	
Sound Power	Operation: 6,9 B (A)	
Noise	Operation: 56 dB (A)	
Mobile and Cloud printing	Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint,	
services	Google Cloud Print	
Power supply	220V, 240V	
ADDITIONAL FEATURES		
Features	Bluetooth	
Panel	Type: Color, Touchscreen, Diagonal: 6,1 cm	
Media Handling	ADF 2-sided copy (A4, plain paper)	
OTHER FEATURES		
Emulations	PCL5e, PCL6	
OTHER		
Warranty		
wairany	12 months On-site service, 100.000 pages	

EcoTank ET-M3180




SUPPLIES

- 111 EcoTank Pigment black ink bottle
- Maintenance Box

LOGISTICS INFORMATION

ѕки	C11CG93402
EAN code	8715946655215
Country of Origin	Philippines
Layer	2 Units

C13T03M140 6.000 pages C13T04D100



EcoTank ET-M3180

* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 19752. 11,000 pages yield based on two ink bottles included with this printer. 6,000 pages yield based on EcoTank ET-MX1XX Series Black Bottle XL ink bottle sold separately. Quoted yields are NOT based on ISO/IEC24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature.

Epson Deutschland GmbH Otto-Hahn-Str. 4 D-40670 Meerbusch Info-Line: 02159 92 79 500 Telefax: +49 (0) 2159/538-3000 www.epson.de Epson in Österreich Info-Line: 01 253 49 78 333 www.epson.at Epson in der Schweiz Info-Line: 022 592 7923 www.epson.ch

1. One year RTB standard warranty, three years RTB warranty by registering your product online.



Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.

Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.