

Power Cord Kit (6 ea), Locking, C13 TO C14 (90 Degree), 0.6m

AP8702R-WW

$\boldsymbol{\Gamma}$		-	-		_		
O	v	е	ľ	٧I	е	v	V

Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this Presentation exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle

or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of

accidentally disconnecting cords and dropping loads.

Lead time

Main

Input Connection Type	IEC 60320 C14
Cable length	0.61 m
Number of cables	6

Provided equipment 3 left-angle jumper cords 3 right-angle jumper cords

Physical

Colour	Black
Height	24 cm
Width	7 cm
Depth	4 cm
Net weight	0.7 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Max line current	10 A
Input current limits	10 A

Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Power cable length	0.61 m

Conformance

Product certifications	CCC PSE		
	VDE		

Environmental

Ambient air temperature for operation	070 °C
Relative humidity	2080 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2575 °C
Storage Relative Humidity	2080 %
Storage altitude	0.0015240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	4 cm
Package 1 Length	7 cm
Package 1 Weight	0.7 kg
Number of Units in Package 3	540

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Lead free	Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Take-back	Take-back program available	

Contractual warranty

Warranty	2 years repair or replace