

Rittal – The System.

Faster – better – everywhere.

Digital enclosure internal temperature display and thermostat – SK 3114.200

Date : Jul 12, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Digital enclosure internal temperature display and thermostat – SK 3114.200

created: 12.07.2021 on www.rittal.com/com-en



Product description	
Description:	For installation in the enclosure door or wall.
Technical specifications:	Three-digit, 7-segment display Option of switching between °C/°F Includes 1800 mm long NTC sensor Two relay outputs as change-over contact and normally open contact (max. contact load 230 V, 6 A) Freely selectable switching difference
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 54
Product description	
Rated operating voltage:	100 V - 230 V, 1~, 50 Hz/60 Hz 24 V - 60 V (DC)
Installation depth:	100 mm
Temperature range:	Operation (environment): +0 °C...+50 °C Setting range: +5 °C...+55 °C
eCl@ss 8.0/8.1:	27210707
Packs of:	1 pc(s).
Weight/pack:	0.26 kg

EAN:	4028177631434
Customs tariff number:	90321020
ETIM 7.0:	EC002014
ETIM 6.0:	EC002014
eCl@ss 8.0/8.1:	27210707
eCl@ss 6.0/6.1:	27210707
Product description:	SK Digital enclosure internal , temperature display and thermostat, 100-230 V, 1~, 50/60 Hz, 24-60 V (DC), Installation depth: 100 mm
Approvals	
Approvals:	CCC exception letter UR
Certificates:	EAC
Declarations:	Declaration of conformity