



Interior installation

Component shelves for attachment to the 482.6 mm (19") system



Component shelf, static installation

482.6 mm (19"), depth-variable for VX IT, TE

For static installation between two 482.6 mm (19") mounting levels.

- Contact width: 489 mm
- Depth-variable to adapt to individual distances between levels
- Tool-free, time-saving one-man assembly

Material:

- Sheet steel

Surface finish:

- Spray-finished

Colour:

- RAL 9005

Supply includes:

- Assembly parts

Distance between levels mm	Load capacity, static kg	Height U	Packs of	Model No.
400 - 600	50	½	1 pc(s).	5501.655
600 - 900	50	½	1 pc(s).	5501.665
400 - 600	100	1	1 pc(s).	5501.695
600 - 900	100	1	1 pc(s).	5501.705

Component shelf, static installation

for TE

The component shelf is attached directly at the side to the front and rear 482.6 mm (19") mounting frames for TE.

Material:

- Sheet steel

Colour:

- RAL 7035

Supply includes:

- Assembly parts

Note:

- Not suitable for combination with telescopic slides

Contact surface, width mm	505
Contact surface, depth mm	410
Distance between 482.6 mm (19") levels mm	495
Load capacity (static) N	300
Packs of	1 pc(s).
Model No.	7000.620

Component shelf, pull-out

482.6 mm (19") for VX IT, TE

For mounting between two 482.6 mm (19") mounting levels.

- Contact width: 419 mm
- Depth-variable to adapt to individual distances between levels
- Tool-free, time-saving one-man assembly from the enclosure front
- Self-locking
- Full withdrawal

Material:

- Sheet steel

Surface finish:

- Component shelf: Spray-finished
- Mounting kit/telescopic slides: Zinc-plated

Colour:

- Component shelf: RAL 9005

Supply includes:

- Component shelf, slotted
- Telescopic slide with mounting kit
- Assembly parts

Distance between levels mm	Load capacity, static kg	Height U	Depth mm	Packs of	Model No.
400 - 600	50	1	500	1 pc(s).	5501.675
600 - 900	50	1	700	1 pc(s).	5501.685
400 - 600	100	1½	500	1 pc(s).	5501.715
600 - 900	100	1½	700	1 pc(s).	5501.725

Accessories:

- Handle for component shelf 5501.730, see page 1011

Interior installation

Component shelves for attachment to the 482.6 mm (19") system

Component shelf, pull-out

for TE

For mounting between two 482.6 mm (19") mounting levels.

Benefits:

- Depth-variable to adjust to the distance between 482.6 mm (19") levels in a 25 mm pitch pattern
- Full withdrawal

Material:

- Base: Sheet steel

Surface finish:

- Base: Spray-finished
- Mounting kit/telescopic slides: Zinc-plated

Colour:

- RAL 7035

Supply includes:

- Component shelf, vented
- Telescopic slides with mounting kit

Contact surface, width mm	409
Contact surface, depth mm	500
Distance between 482.6 mm (19") levels mm	395 – 645
Load capacity (static) N	500
Packs of	1 pc(s).
Model No.	7000.625



Component shelf 1 U, static installation

482.6 mm (19")

for one 482.6 mm (19") mounting level

The ideal support surface for small active components such as modems or mini-hubs.

Load capacity:

- 10 kg surface load, static

Material:

- Sheet steel

Surface finish:

- Spray-finished

Colour:

- RAL 7035

Note:


- Usable height inside the U approx. 35 mm

Component shelf depth mm	Packs of	Model No.
140	1 pc(s).	7119.140



Also required:

- Cage nuts, see page 1002
- Screws, see page 1004



Interior installation

Component shelves for attachment to the 482.6 mm (19") system



Component shelf 2 U, static installation

482.6 mm (19") for one 482.6 mm (19") mounting level

The ideal support surface for small active components such as modems or mini-hubs.

Load capacity:
– 25 kg surface load, static

Material:
– Sheet steel

Surface finish:
– Spray-finished



Component shelf, pull-out, 2 U

for one 482.6 mm (19") mounting level

For simple, front installation of wall-mounted or floor-standing enclosures with at least one 482.6 mm (19") mounting level. This complete set comprises the pre-configured variant including telescopic slides, moulded handle, flange and locking pins.

Benefits:
– Simple tool-free assembly
– Full withdrawal
– Self-locking

Material:
– Sheet steel

Surface finish:
– Spray-finished

Colour:
– RAL 9005

Supply includes:
– Component shelf, pre-configured
– Assembly parts



Component shelf depth mm	Colour	Packs of	Model No.
250	RAL 7035	1 pc(s).	7119.250
	RAL 9005	1 pc(s).	5501.615
400	RAL 7035	1 pc(s).	7119.400
	RAL 9005	1 pc(s).	5501.625



Also required:

- Cage nuts, see page 1002
- Screws, see page 1004

Contact surface, width mm	Contact surface, depth mm	Load capacity (static) N	Packs of	Model No.
430	300	250	1 pc(s).	5501.635