

PARAPROJECT®

MicroCase TC15

Protect , Charge , Transport



Part denomination	PARAPROJECT MicroCase TC15 TwinCharge, USB-C®, without cable, black
Part number	208705151
GTIN /EAN	4006793002890
Field of application	Education
Certificates	CE / REACH / RoHS
Applicable standards	NRL 2011/65/EU / DIN EN 62368-1:2016-05. EMV 2014/35/EU / DIN EN 55022:210+AC:2011 / DIN EN 55035:2010. Rohs 2011/65/EU / DIN EN 50581:2012
Scope of delivery	<ul style="list-style-type: none"> - PARAPROJECT® MicroCase TC15 with integrated TwinCharge technology - device connection cable, EU, length: 5 m - 3 TwinCharge modules with USB-A and USB-C® ports - user guide
Materials	<ul style="list-style-type: none"> - X-ABS plastic - Con-Pearl® - aluminium - industrial leather
Transport	4-fold telescopic handle / 2 carrying handles / 4 smooth-running castors ø 75 mm (with 2 lockable castors)
External dimensions (WxDxH)	530 mm x 360 mm x 450 mm
Weight	10000 g
Transport dimensions	1530 mm x 370 mm x 500 mm
Dimensions of euro-palletts	1200 mm x 800 mm x 1065 mm
Number of euro-pallet	12
customs tariff number	85044083
Country of origin	RO

PARAPROJECT®

MicroCase TC15

Protect , Charge , Transport

Fittings	<ul style="list-style-type: none"> - Interior technical equipment: - 15 storage compartments (W x D x H: 22 x 185 x 270 mm) for iPad/tablets - 3 TwinCharge modules, automatic adjustment via USB-PD Power Delivery and QuickCharge standards - 15 USB-A and USB-C® ports each - 2 active fans - temperature sensor - overvoltage protection - cable protection - Case lid: - 2 pockets with zipper - napped foam - External technical equipment: - central power supply with protective cap - main switch - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors)
Compatible devices	all tablets up to 11" that can be charged by USB-C® or USB-A (QuickCharge, PD)
Max. number of devices	15
Operating system	iOS / Android / Windows
Cable types for equipment	using customer's own USB-C® or USB-A data and charging cables ; USB-C® to USB-C® charging and data cables with a length of 0.3 m are recommended
Power supply	3 TwinCharge modules for the complete power supply of devices
Output power per port	automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; e.g. 15 iPad / Android tablet with 22 W each per port or 12 Surface Go 2 tablet with 30 W each per port ; USB-C® and USB-A output (22 / 30 / 45W): DC ; 5 V / 9 V / 12 V / 15 V -> 3 A; 20 V -> 2,25 A
Optional accessories	<ul style="list-style-type: none"> - data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable with LED display USB-A to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®
Lock types	combination lock
Connections	<ul style="list-style-type: none"> - Outside: - central power supply with protective cap - main switch - Inside: - 15 USB-A and USB-C® ports each, optional depending on the existing charging type
Data of currents	<ul style="list-style-type: none"> - 100 - 240 V - max. 7.5 A - 50/60 Hz
Dimension of pockets	24 x 187 x 270 mm
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm

PARAPROJECT®

MicroCase TC15

Protect , Charge , Transport



- padded case lid
- compartments to store accessories



- storage space for 15 tablets
- TwinCharge technology