PARAPROJECT®

Case TC10 BASKET

Protect , TwinCharge , Transport





Part denomination	PARAPROJECT Case TC10 BASKET TwinCharge, incl. USB-C® to USB-C® cable with LED
Part number	20874015110
GTIN /EAN	4006793005273
Field of application	Education
Certificates	CE / REACH / RoHS
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55035
Scope of delivery	- PARAPROJECT® Case TC10 BASKET with integrated TwinCharge technology - device connection cable, EU, length: 5 m - 2 TwinCharge modules with USB-A and USB-C® ports - 10 data and charging cable with LED display USB-C® to USB-C® - 2 baskets with colored, replaceable padded inserts for carrying handle (red, blue, orange and green) - user guide
Materials	- X-ABS plastic - aluminium - Con-Pearl®
Transport	4-fold telescopic handle / 2 carrying handles / combination lock / 4 smooth-running castors ø 75 mm (with 2 lockable castors)
External dimensions (WxDxH)	530 mm x 390 mm x 495 mm
Weight	11000 g
Transport dimensions	540 mm x 400 mm x 560 mm
Dimensions of euro-plaletts	1200 mm x 800 mm x 1820 mm
Number of euro-pallet	12
customs tariff number	85044083
Country of origin	RO

PARAPROJECT®

Case TC10 BASKET

Protect , TwinCharge , Transport

Fittings	- Interior technical equipment: - Storage compartment (350 x 270 x 320 mm) for 2 removable baskets with 5 compartments each for iPads/tablets - 2 TwinCharge modules, automatic adjustment via USB-PD Power Delivery and QuickCharge standards - 10 USB-A and USB-C® ports each - 10 data and charging cable with LED display USB-C® to USB-C® - temperature sensor - overvoltage protection - Case lid: - napped foam - air vents in the lid and bottom tray - external technical equipment: - central power supply with protective cap - main switch - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors)
Compatible devices	All tablets up to 11,5" that can be charged by USB-C® or USB-A (QuickCharge, PD)
Max. number of devices	10
Operating system	iOS / Android / Windows
Cable types for equipment	USB-C® data and charging cable with USB-C® connector and LED indicator; length: 1.2 m
Power supply	2 TwinCharge modules for the complete power supply of devices
Output power per port	Automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; e.g. 10 iPad / Android tablet with 22 W each per port or 8 Surface Go 2 tablet with 24 W each per port ; USB-C® and USB-A output (22 / 30 / 45 W): DC ; 5 V / 9 V / 12 V / 15 V -› 3 A, 20 V -› 2.25 A
Optional accessories	- data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable with LED display USB-A to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®
Lock types	combination lock
Connections	- Outside: - central power supply with protective cap - main switch - Inside: - 10 USB-A and USB-C® ports each, optional depending on the existing charging type
Data of currents	- 100 - 240 V - max. 5 A - 50/60 Hz
Dimension of pockets	350 x 270 x 320 mm
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm

PARAPROJECT®

Case TC10 BASKET

Protect , TwinCharge , Transport







-