Key **Features**

- Integrated USB TypeC and Ethernet
- Daisy chain monitor
- Ergonomic design
- vDisplay Manager software for multitasking
- Lower total cost of ownership



Product **Description**

The ViewSonic VG56 docking monitor series will keep the workstation tidy and productive with USB Type-C and Ethernet connectivity that turn your monitor into a hub for charging, data, network, and devices. With a 27" display and 2560 X 1440 resolution that delivers larger and clearer images, the VG2756 QHD monitor expands your productivity. This monitor's DisplayPort output also makes it convenient to daisy chain monitors, reducing clutter on your desk and simplifying cable management. A range of ergonomic features such as 40-degree tilt, swivel, bi-directional pivot and height adjustment, along with eye-care technology let you stay comfortable at work all day. In addition, the supported vDisplay Manager software for multi-tasking provides efficient on-screen display control. The monitor and quick release stand ship in an eco-friendly, biodegradable package, thus minimizing total cost of ownership.

Visit Us

www.viewsonic.com

DISPLAY		INPUT SIGNAL	
Display Size (in.):	27	Frequency Horizontal:	15 ~ 90KHz
Viewable Area (in.):	27	Frequency Vertical:	49 ~ 75Hz
Panel Type:	IPS Technology	VIDEO INPUT	
Resolution:	2560 x 1440	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet -
Resolution Type:	QHD (Quad HD)	,	Type Č
Static Contrast Ratio:	1,000:1 (typ)	ERGONOMICS	
Dynamic Contrast Ratio:	80M:1	Height Adjust (mm):	130
Light Source:	LED	Swivel:	120°
Brightness:	350 cd/m² (typ)	Tilt (Forward/Back):	-5° / 40°
Colors:	16.7M	Pivot (Right/Left):	90° / 90°
Color Space Support:	8 bit true	WEIGHT (IMPERIAL)	
Aspect Ratio:	16:9	Net (lbs):	15.2
Response Time (Typical GTG):	5ms	Net Without Stand (lbs):	9.9
Response Time (GTG w/OD):	5.8ms	Gross (lbs):	22.5
Viewing Angles:	178° horizontal, 178° vertical	WEIGHT (METRIC)	
Backlight Life (Hours):	30000 Hrs (Min)	Net (kg):	6.9
Curvature:	Flat	Net Without Stand (kg):	4.5
	60	Gross (kg):	10.2
Refresh Rate (Hz):		DIMENSIONS (IMPERIAL) (W	/XHXD)
Blue Light Filter:	Yes	Packaging (in.):	27.2 x 16.9 x 8.6
Flicker-Free:	Yes	Physical (in.):	24.1 x 15.99~20.99 x 8
Color Gamut:	NTSC: 78% size (Typ) sRGB: 110% size / 100% coverage (Typ)	Physical Without Stand (in.):	24.1 x 14.2 x 2
		DIMENSIONS (METRIC) (WX	HXD)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Packaging (mm):	692 x 430 x 218
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical (mm):	612 x 406.19~533.24 x 202
COMPATIBILITY		Physical Without Stand (mm):	612 x 362 x 52
PC Resolution (max):	2560x1440	GENERAL	
Mac® Resolution (max):	2560x1440	cTUVus, FCC-B, ICES003, Energy	
PC Operating System:	Windows 11 certified; macOS tested	Regulations:	Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS,
Mac® Resolution (min): CONNECTOR	2560x1440	ErP, ŘEACH, WEEE, TCO UkrSEPRO, UKCA, RCM	
USB 3.2 Type A Down Stream:	2		VG2756-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable
USB 3.2 Type B Up Stream:	1	PACKAGE CONTENTS: Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1	
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (90W power charger)		
HDMI 1.4:	1	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
DisplayPort:	1	Warranty:	*Warranty offered may differ from
DisplayPort Out:	1	warranty.	market to market
Power in:	3-pin Socket (IEC C14 / CEE22)	Power Management:	Energy Star standards, EPEAT
Ethernet LAN (RJ45): AUDIO	1		
Internal Speakers:	2Watts x2		
POWER	a //_		
Eco Mode (Conserve):	16.81W		
Eco Mode (optimized):	21.12W		
Consumption (typical):	26.35W		
Consumption (max):	35.94W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE	,		
Kensington Lock Slot:	1		
Cable Organization: CONTROLS	Yes		
Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS	iliage Aujust, Setup Menu		
	32°E to 104°E (0°C to 40°C)		
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT	100 v 100 mm		

100 x 100 mm

VESA Compatible: