

Mini DisplayPort to VGA Adapter with Audio

Product ID: MDP2VGAA



This unique Mini DisplayPort[™] to VGA adapter is equipped with a built-in audio port which lets you connect Mini DisplayPort equipped devices, such as a Microsoft® Surface[™] Pro devices or MacBook Air laptop, to a VGA display or projector with audio.

Share your presentations and videos

Because most boardrooms are set up differently, the length of cables available in each room vary. Not all laptops have the Mini DisplayPort (mDP) and audio ports positioned on the same side, which can become awkward when you're trying to share your presentations. It can also mean that some ports may be just out of reach during a meeting.

This convenient adapter positions your audio and video ports on the same side of your laptop, to ensure that all of the ports you need are accessible when you need them.

www.startech.com 1 800 265 1844



Data Sheet

Substitute for a damaged audio port

If the audio port on your mobile device is damaged or blocked by other connections, this convenient adapter guarantees that you'll always have all of the ports you need for every presentation. By connecting audio to your laptop through the adapter, you can be prepared for any situation.

In order to use the audio function of the adapter you need to power the adapter through a USB port on your laptop, or through a charge port on a USB grommet. Simply plug a Micro USB cable from the adapter into the USB port and audio will be available when you deliver your presentation.

Create a clutter-free environment

The adapter can also be used for connecting your laptop or desktop computer to your monitor and speakers. The adapter and connected cables can be placed nicely at the back of your monitor to create a tidy setup between all of your devices.

Arrive prepared, wherever you go

This mDP to VGA adapter is extremely portable with a lightweight, small-footprint design. It's the perfect accessory to carry with your mobile devices, fitting easily into your laptop bag or carrying case. Its ultraportable design makes the adapter ideal for BYOD (Bring Your Own Device) applications at the office.

It also enables you to arrive prepared when you're presenting to a potential client, teaching off-site, or traveling to a meet with a customer.

The adapter is compatible with Intel® Thunderbolt[™], when connected directly to a supporting DisplayPort over Thunderbolt[™] I/O port, and supports resolutions up to 1920x1200 (WUXGA).

The MDP2VGAA is backed by a 3-year StarTech.com warranty and free lifetime technical support.

www.startech.com 1 800 265 1844



Data Sheet

Certifications, Reports and Compatibility





− C € F©

Applications

- Connect a VGA monitor or projector to a Mini DisplayPort equipped device, while providing audio for your video presentations
- Connect a VGA display to your mDP laptop to use as a secondary monitor
- Keep the adapter with you while traveling, to connect to any VGA monitor or projector you come across
- Walk into any boardroom with your Mini DisplayPort laptop or tablet and be ready to present

Features

- Group your VGA and audio ports together, to ensure they're all accessible when you need them
- Substitute a damaged or blocked audio port by connecting your audio directly through the adapter
- Provide crystal-clear picture quality with support for high-definition video resolutions up to 1920x1200 or 1080p
- Maximum portability with a small footprint and lightweight design



StarTechcom

Hard-to-find made easy*

Data Sheet

	Warranty	3 Years
Hardware	Active or Passive Adapter	Active
	Adapter Style	Adapters
	Audio	Yes
	AV Input	Mini-DisplayPort
	AV Output	VGA
Performance	Audio Specifications	2-channel stereo (3.5mm)
	Maximum Analog Resolutions	1920x1200 / 1080p (output)
	Maximum Digital Resolutions	1920x1200 / 1080p (input)
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - Mini-DisplayPort (20 pin) Male Input
	Connector B	1 - VGA (15 pin, High Density D-Sub) Female Output
		1 - 3.5 mm Mini-Jack (3 Position) Female Output
	Connector Type(s)	1 - USB Micro-B (5 pin) Female Input
Power	Power Source	USB-Powered
Environmental	Humidity	40%~50%RH
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-10°C to 55°C (14°F to 131°F)
Physical Characteristics	Cable Length	7.2 in [18.4 cm]
	Color	Black
	Product Height	0.6 in [16 mm]
	Product Length	12 in [305 mm]
	Product Weight	1.6 oz [44.4 g]
	Product Width	1.7 in [44 mm]
Packaging Information	Package Quantity	1
	Shipping (Package) Weight	2 oz [58 g]
What's in the Box	Included in Package	1 - Mini DisplayPort to VGA adapter
		1 - 0.25m Micro USB cable

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844