



# 0.5m USB 3.2 Type C Cable, 2 x 90° Right Angle, 10Gbps

32022

---

## TITLE EN

0.5m USB 3.2 Type C Cable, 2 x 90° Right Angle, 10Gbps

---

## SUBTITLE EN

USB Type C Male to Male

---

## SHORT DESCRIPTION EN

- Entry level USB 3.2 Type C cable for home and small office applications
- Both USB Type C plugs are angled at 90°
- Supports data rates of up to 10Gbps
- Robust PVC housing with nickel-plated contacts
- 10 year warranty

LINDY USB 3.2 Type C cables feature double shielded construction with copper conductors for premium performance and corrosion resistance. Nickel connectors and gold plated contacts maintain signal integrity and reliability.

USB cables with angled plugs protect the USB ports of your devices by reducing pressure and preventing cable breakage, making them ideal for confined spaces and hard-to-reach ports.

Data transfer speeds up to 10Gbps are supported for the quick and effortless transfer of large data volumes.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

USB 3.2 Type C, 2 x 90° Right Angle cables are available in the following lengths: 0.5m, 1m, 1.5m.

### Connectors

- Connector A: USB 3.2 Type C Male 90° Right Angle
- Connector B: USB 3.2 Type C Male 90° Right Angle
- Housing Material: PVC
- Shielding in head shell: -
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions (approx.) WxDxH: 11.1x25.8x24.2mm (0.44x1.02x0.95in)

### Cable Construction

- Length: 0.5m (1.64ft)
- Standard: USB 3.2 Gen 2 (USB 3.1 Gen 2, USB 3.1)
- Power Delivery: PD 2.0
- Max. Power: 60W
- Colour: Black
- Type: Round
- Jacket Diameter: 5mm (0.2in)
- Jacket Material: PVC
- Conductor Material: Copper
- Conductor Gauge Power: 22 AWG
- Conductor Gauge Data: 28 AWG
- Shielding: Aluminium Foil 110%

### Specifications

- Supported Bandwidth: 10Gbps
- Nominal Attenuation: 0.5Mhz- 400Mhz < 5.8db
- Minimum Bend Radius: 50mm (1.97in)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: 0°C - 70°C (32°F - 158°F)

### Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Product Compliance: RoHS, REACH, California Proposition 65

### Purchasing Information

- No.: 32022
- EAN: 4002888320221

### This product is also available in other lengths

- 32022 - 0.5m (1.64ft)
- 32023 - 1m (3.28ft)
- 32024 - 1.5m (4.92ft)