Rittal - The System.

Faster – better – everywhere.

CMC III CAN bus connection cable – DK 7030.091

Date: Jul 12, 202



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

CMC III CAN bus connection cable - DK 7030.091

created: 12.07.2021 on www.rittal.com/com-en



Product description

Description:	For connecting the PU to the CAN bus sensors III, units III and control units III as a bus, also for cabling together. Because it is available in different lengths, the CMC III system can be adapted to various applications and built to a custom design.
Applications:	For connecting the CAN bus units. Information and power transfer of the individual CAN bus units.
Product descript	ion
Dimensions:	Length: 1 m
Operating temperature:	Operation (environment): +0 °C+55 °C

Dimensions:	Length: 1 m
Operating temperature:	Operation (environment): +0 °C+55 °C
Ambient humidity (non-condensing):	Operation (environment): 5 % - 95 %
Interfaces/connections:	Connector (type): RJ45 Connector (type): RJ45
Packs of:	1 pc(s).
Weight/pack:	0.05 kg
Copper weight (kg per piece):	0
EAN:	4028177659421
Customs tariff number:	85444290

© Rittal 2021

ETIM 7.0:	EC000313
ETIM 6.0:	EC000313
e Cl@ss 8.0/8.1:	27189253
e Cl@ss 6.0/6.1:	27189253
Product description:	DK CMC III CAN bus connection cable, L: 1 m, type: RJ45
Approvals	
Certificates:	NA

© Rittal 2021 2