



## Reliable, tough & jobsite-tested labels for industrial applications.

DYMO Industrial labels are heat, chemical and UV-resistant, and backed by industrial-strength adhesives that stick and stay stuck in harsh conditions.

## The Right Label For The Right Application



VINYL	PERMANENT POLYESTER	FLEXIBLE NYLON	HEAT-SHRINK TUBE	SELF-LAMINATING
Available in the widest range of colors, ideal for flat or curved surfaces in both indoor and outdoor applications	Intended for flat surfaces or flanges and features a polished finish	Flexible & tear proof Ideal for wires, cables, curved or textured surfaces	High end cable identification 3:1 shrink ratio	Oil, solvent and water resistant

### Vinyl

Temperature rating: -40°C to 80°C



9 mm x 5.5 m 3/8" x 18"	12 mm x 5.5 m 1/2" x 18"	19 mm x 5.5 m 3/4" x 18"	24 mm x 5.5 m 1" x 18"
----------------------------	-----------------------------	-----------------------------	---------------------------

### Permanent Polyester

Temperature rating: -40°C to 150°C



6 mm x 5.5 m 1/4" x 18"	9 mm x 5.5 m 3/8" x 18"	12 mm x 5.5 m 1/2" x 18"	19 mm x 5.5 m 3/4" x 18"	24 mm x 5.5 m 1" x 18"
----------------------------	----------------------------	-----------------------------	-----------------------------	---------------------------

### Flexible Nylon

Temperature rating: -40°C to 60°C



12 mm x 5.5 m 1/2" x 18"	19 mm x 5.5 m 3/4" x 18"	24 mm x 5.5 m 1" x 18"
-----------------------------	-----------------------------	---------------------------

### Heat-Shrink Tube

Temperature rating: Up to 125°C



6 mm x 5.5 m 1/4" x 18"	9 mm x 5.5 m 3/8" x 18"	12 mm x 5.5 m 1/2" x 18"	19 mm x 5.5 m 3/4" x 18"	24 mm x 5.5 m 1" x 18"
----------------------------	----------------------------	-----------------------------	-----------------------------	---------------------------