



Acer CB2 series

Acer CB342CKCsmiiphuzx

For those who want more

The Acer CB2-Series is perfect for daily work. The height adjustment helps to relax your neck and the optional Pivot-Function facilitate reading PDF- and text documents.

The stylish frameless zero- frame design fits in any environment perfectly, does not matter if it is the office or at home on the desk. The latest intersections top the package off and enable an excellent integration in the existing infrastructure.



- Diagonal size: 86.4 cm (34.0 inches)
- Resolution (native): 3,440 x 1,440
- Response time: 1 ms
- Brightness: 400 cd/m²
- Signal input: 2x HDMI 1x DP USB Hub Audio Out





Technical Specifications

Diagonal size	86.4 cm (34.0 inches)
Active display area (WxH)	796 x 333 mm
Resolution (native)	3,440 x 1,440
Aspect ratio	21:9
Pixel pitch (PPI)	0.232 mm (109.7)
Panel type	IPS Technology
Response time	1 ms
Brightness	400 cd/m ²
Backlight type	LED
Acer CrystalBrite	No, anti-glare display
Viewing angle (h/v) CR>10:1	178°/178°
Viewing angle (h/v) CR>5:1	178°/178°
Static contrast ratio	1000:1
Dynamic contrast ratio	100M:1
Colors	16.7M
Speaker	2 x 3 watts
Signal input	2x HDMI 1x DP USB Hub Audio Out
Frequency (H/V)	15KHz~222KHz / 48Hz~76Hz
Refresh rate (max.)	75 Hz
HDMI	2x HDMI (2.0)
DisplayPort	1x (DP 1.4)
VGA	-
DVI	-
USB 3.1 Type-C	-
USB Hub	Yes (USB 3.0, 1x up and 3x down)
Audio	1x Out

Dimensions and weight

Dimension (W x H x D)	817 x 447.0 - 597.0 x 269 mm
Min. thickness without stand	58.60 mm
Weight (unpacked)	8.70 kg
Weight (packed)	12.20 kg
Pallet qty and size (H x W x D)	20 Pcs (197.5 x 93.0 x 117.0 cm)
Container loading (20'/40')	220 / 440

Others

Storage ambient temperature	No
-----------------------------	----

Ordering Information

Model	CB342CKCsmiiphuzx
Part number	UM.CB2EE.C01
EAN	4710180791792

Power supply and consumption

Power supply	Internal
--------------	----------

ErgoStand

Tilt angle	-5°~35°
Swivel angle	360°
Height adjust range	150 mm
VESA wall mounting	100x100 mm

Norms and Standards

Warranty	36 Months Carry In
Certification	MPR-II
MTBF	30,000 h at 25°C