

Product datasheet

Specifications



Rack PDU, Basic, Zero U, 16A, 208/230V, (15) C13

AP9572



Overview

Lead time

Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	200 V 208 V 230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	0U
Cable length	2.50 m
Number of cables	1
Provided equipment	Rack mounting brackets Toolless mounting kit User manual

Physical

Colour	Black
Height	62 cm
Width	4.4 cm
Depth	4.4 cm
Net weight	2 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Max line current	16 A
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Output

Number of power socket outlets 15 IEC 60320 C13

Conformance

Product certifications	cUL listed CE Queensland Australia UL listed VDE
Standards	UL 60950

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	63.8 cm
Package 1 Width	16.8 cm
Package 1 Length	14.6 cm
Package 1 Weight	2.724 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace