



LANCOM GS-2326+

Managed 26-port Gigabit Ethernet switch for reliable networks

The LANCOM GS-2326+ is a reliable component for modern network infrastructures for any industry or application. It networks up to 26 devices with its 24 Gigabit Ethernet ports and 2 combo ports (Ethernet or fiber-optic). Equipped with numerous security features and a high-performance hardware platform, it is ideal for the secure and reliable networking of medium-sized networks.

- › 24 Gigabit Ethernet and 2 combo ports (TP/SFP)
- › Energy-saving functions based on IEEE 802.3az with port deactivation if no data is transferred
- › Security with configurable access control on all ports as per IEEE 802.1X
- › Secure remote management through TACACS+, SSH, SSL, and SNMPv3
- › Convenient integration into LANCOM monitoring systems
- › IPv6 and IPv4 support for modern enterprise networks
- › 5-year warranty on all components

LANCOM GS-2326+

High power output on 26 ports

The LANCOM GS-2326+ is equipped with 24 Gigabit Ethernet ports and 2 combo ports (Ethernet or fiber-optic). With a data throughput of 52 Gbps on the backplane, it offers full performance even under load. This makes the switch a high-performance basis for modern network infrastructures in any industry or field of application.

Configurable access control

The LANCOM GS-2326+ excludes rogue clients from gaining unauthorized access to the network. This is ensured by secured access control on all ports as per IEEE 802.1X (port-based, single, multi, and MAC-based).

Secure remote management

Secure communication protocols such as SSH, SSL and SNMPv3 mean that the LANCOM GS-2326+ is ideal for professional remote network management. The switch also supports the TACACS+ protocol for authentication, authorization, and accounting. This optimized solution promises maximum security for multi-site network management and monitoring.

Integration into LANCOM monitoring systems

The LANCOM GS-2326+ integrates seamlessly into existing LANCOM network infrastructures. Network events are easy to monitor with the LANCOM monitoring systems LANCOM Large Scale Monitor and LANmonitor.

IPv6 and IPv4 support

Thanks to the dual-stack implementation, the LANCOM GS-2326+ operates in pure IPv4, pure IPv6, or in mixed networks. Applications such as SSL, SSH, Telnet, and TFTP can continue to be operated on IPv6 networks. Supported IPv6 features include stateless auto-configuration, the discovery of neighboring devices, and MLD snooping.

LANCOM GS-2326+

Quality of Service	
Priority queues	Supports eight hardware priority queues to prioritize inbound and outbound traffic
Scheduling	Strict priority and weighted round-robin (WRR); queue assignment based on DSCP and class of service (IEEE 802.1p/CoS)
Classification	Port based, IEEE 802.1p VLAN priority; IPv4/IPv6 Precedence; Priority queuing of packets based on DSCP/ToS/DiffServ; classification and re-marking with ACLs, trusted QoS
Rate limiting	Ingress policer; egress shaping and rate control; control per VLAN, per port and flow based
Security	
Secure Shell Protocol (SSH)	SSH to secure incoming/outgoing Telnet connections
Secure Sockets Layer (SSL)	SSL to encrypt HTTP connections; advanced security for browser-based configuration via web interface
IEEE 802.1X	IEEE 802.1X access control on all ports; RADIUS for authentication, authorization and accounting with MD5 hashing; guest VLAN; dynamic VLAN assignment
Private VLAN edge	Layer 2 isolation between clients in the same VLAN ("protected ports"); support multiple uplinks
Port security	Locking of MAC addresses to ports; limiting of the number of learned MAC addresses
IP source guard	Blocking access for illegal IP addresses on specific ports
Access control lists	Drop or rate limitation of connections based on source and destination MAC addresses, VLAN ID, IP address, protocol, port, DSCP/IP precedence, TCP/UDP source and destination ports, IEEE 802.1p priority, ICMP packets, IGMP packets, TCP flag
RADIUS/TACACS+	Authentication, authorization and accounting of configuration changes by RADIUS or TACACS+
Storm Control	Multicast/Broadcast/Unicast storm suppression
Isolated Group	Allows certain ports to be designated as protected. All other ports are non-isolated. Traffic between isolated group members is blocked. Traffic can only be sent from isolated group to non-isolated group.
Performance	
Switching technology	Store and forward with latency less than 4 microseconds
MAC addresses	Support of max 8K MAC addresses
Throughput	Max. 52 Gbps on the backplane
Maximum packet processing	38.69 million packets per second (mpps) at 64-byte packets
Single IP Management (SIP)	Supports stacking of up to 16 devices, several switches can be managed via one ip address
VLAN	Port based and IEEE 802.1q tag based VLAN with up to 4,096 VLAN and up to 4,000 active VLANs; Supports ingress and egress packet filter in port based VLAN
Jumbo frame support	Jumbo frame support with up to 9k frames
Energy efficiency (Green Ethernet)	
Energy detection	Energy efficiency according to IEEE 802.3az. Automatically turns off power on Gigabit Ethernet RJ-45 port when detecting link down or Idle of client. Active mode is resumed without loss of any packets when the switch detects the link up
Cable length detection	Adjusts the signal strength based on the cable length. Reduces the power consumption for short cable
Layer 2 switching	
Link Aggregation Control Protocol (LACP)	Support of 13 groups containing up to 16 ports each according to IEEE 802.3ad
VLAN	Support for up to 4K VLANs simultaneously (out of 4096 VLAN Ids); matching due to port, IEEE 802.1q tagged VLANs or MAC addresses
Voice VLAN	Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS
IGMP multicasts	IGMP v1, v2, v3 to limit bandwidth-intensive multicast traffic to ports with requesters; supports 256 multicast groups; source-specific multicasting
IGMP querier	Support of multicast domains of snooping switches in the absence of a multicast router
IGMP proxy	IGMP proxy to pass IGMP messages through
Generic VLAN registration	VLAN registration with GVRP according to IEEE 802.1q for automatic delivery of VLANs in bridged domains

LANCOM GS-2326+

Layer 2 switching	
Spanning Tree Protokoll (STP) / Rapid STP / Multiple STP	Standard Spanning Tree according to IEEE 802.1d with fast convergence support of IEEE 802.1w (RSTP); using Multiple Spanning Tree instances by default according to IEEE 802.1s (MSTP)
DHCP Relay Agent	DHCP relay agent, supporting DHCP option 82
LLDP	Automatic discovery of network topology in layer 2 networks (Link Layer Discover Protocol) according to IEEE 802.1AB with LLDP-MED extensions
IPv6	
IPv4/IPv6 dual stack	IPv4 and IPv6 in parallel to support migration
IPv6 mechanisms	<ul style="list-style-type: none"> ■ IPv6 host mode ■ Dual IPv6/ IPv4 stack ■ IPv6 neighbor and router discovery (ND) ■ IPv6 stateless address auto-configuration ■ Path maximum transmission unit (MTU) discovery ■ Duplicate address detection (DAD) ■ ICMP version6
IPv6 QoS	Prioritization of IPv6 packets in hardware
IPv6 ACL	Drop or rate limiting of IPv6 packets due to ACLs in hardware
Multicast Listener Discovery	MLD snooping to limit multicast packets to ports with receivers
IPv6 services	Web interface/SSL, Telnet/SSH, ping, Simple Network Time Protocol (SNTP), Trivial File Transfer Protocol (TFTP), SNMP, RADIUS, SYSLOG, DNS Client, protocol-based VLANs
Interfaces	
Ethernet	<ul style="list-style-type: none"> ■ 24 TP ports 10/100/1000 mbps ■ 2 Combo ports (TP/SFP) with 100/1000 mbps (SFP) and 10/100/1000 mbps (TP) ■ 26 concurrent Ethernet ports in total
Console port	RJ45 configuration port for command line access
Management and monitoring	
WEBconfig	Integrated web server with setup wizard for the configuration via Internet browsers with HTTP or HTTPS. Web interface with system dashboard, configuration menu, maintenance and monitoring functions
LANconfig	Supported by LANconfig (LANCOM management software): automatic detection, display of device properties, opening of web configuration
Large Scale Monitor (LSM)	The LANCOM Large Scale Monitor (LSM) is a professional tool for monitoring medium-sized to large-scale networks with 25 to 1,000 network components. Designed especially for LANCOM components including WLAN access points, controllers, switches, and routers, this system based on open-source components additionally allows for the monitoring of third-party products such as servers and printers. Problems in the network are clearly displayed in tables or graphical floor plans, and they trigger alert messages via e-mail if certain threshold values are not maintained.
LANmonitor	Monitoring application for Microsoft Windows for (remote) surveillance and logging of the device and port status
Easy-Configuration-Ports	Easy setup of ports for QoS and Security based on pre-defined configuration profiles
Port Mirroring	Traffic can be mirrored from on port to another for investigation with network analyzer or RMON probe. Up to 8 ports can be mirrored to a single mirror port. Single sessions can be selected
Security	Access rights (read/write) can be set up separately, access control list
SNMP	SNMP management via SNMPv1, v2c or v3 with support of traps. User-based security model for SNMPv3 (USM)
Diagnosis	Diagnosis from the switch with PING and cable diagnosis

LANCOM GS-2326+

Management and monitoring	
Command Line Interface (CLI)	Configuration and status display from the command line with console application and direct connection to console port, via Telnet or SSH
Remote Monitoring	Integrated RMON software agent supports 4 RMON groups (history, statistics, alarms and events) for enhanced traffic management, monitoring and analysis
Firmware update	<ul style="list-style-type: none"> ■ Update via WEBconfig and browser (HTTP/HTTPS) ■ Update via TFTP and LANconfig ■ Dual firmware image to update during operation
Secure Copy	Securely import and export files
DHCP client	Automatic assignement of the management IP address by DHCP
SNTP	Automatic time settings with Simple Network Time Protocol (SNTP)
s-flow	Standard for monitoring of high-speed-networks. Visualization of network use, accounting an anlysatation to protect your network against dangers
Hardware	
Weight	5,50 lbs (2,50 kg)
Power supply	Internal power supply unit (110–230 V, 50-60 Hz)
Environment	Temperature range 0–40° C; humidity 10–90%; non-condensing
Housing	Robust metal housing, 19' 1U (442 x 44 x 170,3 mm > W x H x D) with removable mounting brackets, network connectors on the front
Fans	None; fanless design without rotating parts, high MTBF
Power consumption (max)	26 Watts
Declarations of conformity*	
CE	EN 60950-1, EN 55022, EN 55024
FCC	FCC Part 15 (CFR47) Class A
*) Note	You will find all declarations of conformity in the products section of our website at www.lancom-systems.eu
Supported IEEE standards	
IEEE 802.1AB	Link Layer Discovery Protocol (LLDP)
IEEE 802.1AB	LLDP-MED
IEEE 802.1ad	Q-in-Q tagging
IEEE 802.1d	MAC Bridging
IEEE 802.1d	Spanning Tree
IEEE 802.1p	Class of Service
IEEE 802.1q	VLAN
IEEE 802.1s	Multiple Spanning Tree Protocol (MSTP)
IEEE 802.1w	Rapid Spanning Tree Protocoll (RSTP)
IEEE 802.1X	Port Based Network Access Control
IEEE 802.3	10Base-T Ethernet
IEEE 802.3ab	1000Base-TX Ethernet
IEEE 802.3ad	Link Aggregation Control Protocol (LACP)
IEEE 802.3az	Energy Efficient Ethernet
IEEE 802.3u	100Base-T Ethernet

LANCOM GS-2326+

Supported IEEE standards

IEEE 802.3x	Flow Control
IEEE 802.3z	1000Base-X Ethernet

Supported RFC standards

RFC 854	Telnet Protocol Specification
RFC 1213	MIB II
RFC 1215	SNMP Generic Traps
RFC 1493	Bridge MIB
RFC 1769	Simple Network Time Protocol (SNMP)
RFC2021	Remot Network Monitoring MIB v2 (RMONv2)
RFC 2233	Interface MIB
RFC 2613	SMON MIB
RFC 2617	HTTP Authentication
RFC 2665	Ethernet-Like MIB
RFC 2674	IEEE 802.1p and IEEE 802.1q Bridge MIB
RFC 2818	Hypertext Transfer Protocol Secure (HTTPS)
RFC 2819	Remote Network Monitoring MIB (RMON)
RFC 2863	Interface Group MIB using SMIv2
RFC 2933	IGMP MIB
RFC 3019	MLDv1 MIB
RFC 3414	User based Security Model for SNMPv3
RFC 3415	View based Access Control Model for SNMP
RFC 3635	Ethernet-Like MIB
RFC 3636	IEEE 802.3 MAU MIB
RFC 4133	Entity MIBv3
RFC 4188	Bridge MIB
RFC 4251	The Secure Shell Protocol Architecture (SSH)
RFC 4668	RADIUS Authentication Client MIB
RFC 4670	RADIUS Accounting MIB
RFC 5519	Multicast Group Membership Discovery MIB

Scope of delivery

Manual	Printed Installation Guide (DE/EN)
Cable	Serial configuration cable, 1.5m
Cable	IEC power cord
19" brackets	Two 19" brackets for rackmounting

Support

Warranty	5 years, support via hotline and Internet KnowledgeBase
LANCOM Warranty Advanced Option S	Option to extend the manufacturer's warranty from 3 to 5 years and replacement of a defective device on the next working day, item no. 10715

Accessories

1000Base-SX SFP module	LANCOM SFP-SX-LC1, item no. 61556
------------------------	-----------------------------------

LANCOM GS-2326+

Accessories

1000Base-LX SFP module	LANCOM SFP-LX-LC1, item no. 61557
------------------------	-----------------------------------

Item number(s)

LANCOM GS-2326+ (EU)	61483 (EU)
LANCOM GS-2326+ (UK)	61484 (UK)