

Rittal – The System.

Faster – better – everywhere.

FlatBox – DK 7507.110

Date : Dec 7, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



FlatBox – DK 7507.110

created: 07.12.2020 on www.rittal.com/com-en



Product description

Design: with 482.6 mm (19") mounting angles

Description: For flexible use as a wall-mounted or floor-standing enclosure.

Benefits: Tool-free quick assembly
System assembly on the open 482.6 mm (19") frame

Material: Sheet steel
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Colour: RAL 7035

Supply includes: Flat-packed enclosure
1 wall section
2 basic supports
2 roof/base plates, with cut-outs for cable entry via brush strips
2 side panels, lockable
1 glazed door, lockable, security lock 3524 E, door hinge point selectable
Connection components for tool-free, fast assembly
Earthing kit for system-compatible earthing of all enclosure parts
482.6 mm (19") mounting angles

Note: Max. installation depth: Depth - 58 mm to rear panel
Max. distance between two 482.6 mm (19") levels: Depth - 104 mm

Basic material: Sheet steel

Product features

Dimensions:	Width: 600 mm Height: 492 mm Depth: 600 mm
Installation height for components:	9 U
Load capacity:	max. 450 N
Packs of:	1 pc(s).
Weight/pack:	27 kg
EAN:	4028177551442
Customs tariff number:	94032080
ETIM 7.0:	EC002500
ETIM 6.0:	EC002500
eCl@ss 8.0/8.1:	27180208
eCl@ss 6.0/6.1:	27180208
Product description:	DK FlatBox, WHD: 600x492x600 mm, 9 U, with 482.6 mm (19") mounting angles
Approvals	
Certificates:	EAC