

## Key Features

- Windows 10 Pro (ViewSonic recommends Windows 11 Pro for business) \*
- Ideal Integrated Solution for ViewBoard® Interactive Displays & Commercial Displays
- Powerful Intel® 10th Core Processors
- Improved System Stability, Security, & Thermal Control



## Product Description

Seize the power to get more done when you sync your ViewBoard® interactive displays and wireless presentation display with the ViewSonic VPC25-W33-O1-1B slot-in PC. Integrated with exceptional performance from Intel® 10th Gen Core™ processors, up to 8GB DDR4 memory, and up to 256GB of SSD storage, experience enhances computing performance to breeze through complex classes and collaborations. Plug into pure productivity with dual-band WiFi, Bluetooth 5.2, and a range of ports, including 4K HDMI, DP1.2, USB 3.2, and Gigabit LAN RJ45 for faster workflows.



1. HDD/Power LED
2. LINE-OUT
3. MIC-IN
4. Power Button
5. HDMI
6. Type C
7. DP

8. USB 2.0
9. Reset
10. USB 3.2
11. LAN

---

**Visit Us**

[www.viewsonic.com](http://www.viewsonic.com)

## CORE

CPU:	Intel Core i5-10400T 2.0GHz Turbo boost 3.6GHz
Graphics:	Integrated Intel® UHD graphic 610 Intel H510 chipset

## MEMORY

Capacity:	8GB DDR4
-----------	----------

## SOFTWARE

Operating System:	Windows 10 Pro (ViewSonic recommends Windows 11 Pro for business)*
-------------------	---

## STORAGE

Dimension:	M.2 2280 (22 x 80 mm)
Capacity:	256GB SSD
Interface:	M.2 2280 NVMe PCIe Gen3 SSD

## INPUT

MIC(Microphone):	x1
------------------	----

## OUTPUT

DisplayPort:	x 1 (1.2, resolution 3840x2160@60Hz)
HDMI:	x 1 (1.4, resolution 3840x2160@60Hz)
Audio:	x 1 Line out

## LAN

RJ45:	GbE LAN Port
-------	--------------

## WIRELESS / BLUETOOTH

Intel AX200 WiFi 6 + BT5.2 Module dual band
---

## USB

Type A:	USB x 4 (USB 3.2 x 1, USB 2.0 x 3)
Type C:	x 1 (data only)

## BUNDLE SOFTWARE

Adobe Reader /myViewBoard WhiteBoard /WatchDog / Winflash
--

## POWER

Voltage:	DC in +12V~+19V @ 3.42A
Consumption:	65 W (Typical)

## OPERATING CONDITIONS

Temperature (° C):	-5~45°C
Humidity:	20% ~ 80% R.H. Non- Condensing

## DIMENSIONS (W X H X D)

Physical (inch / mm):	7.95" x 4.69" x 1.18" / 202 x 119 x 30 mm
Packaging (inch / mm):	10.00" x 7.72" x 3.03"/254 x 196 x 77 mm

## WEIGHT

Net (lb / kg):	2.205 lb/1 kg
Gross (lb / kg):	2.646 lb/1.2 kg

## REGULATIONS

cTUVus, FCC-B w/ ICES003, FCC ID+SDOC, CA IC, IC  
VOC, NOM, COFETEL, CE EMC, CE RED, CE LVD, CB,  
RoHS, REACH, WEEE, BSMI, NCC, BIS, WPC, RCM,  
MIC, VCCI, VNTA, CCC, SRRC

## PACKAGE CONTENTS

1. VPC OPS2. Quick Start Guide3. Screw x 2