



## Technical specifications

### Features

Weekly schedule with up to eight switching points a day

Button for changing the room temperature

Intuitive setup in the browser-based FRITZ!Box user interface

manually	Control via PC, notebook, smartphone or tablet – or on the go, online and with the FRITZ!App Smart Home
Function keys for antifreeze and boost (fast heating)	
Vacation switching	Display content can be rotated in 90 degree steps
Group switching (multiple FRITZ!DECT 302 and/or 301 are combined in a group/room)	Configurable open window detection
Configurable temperature offset	Keylock – separately for radiator control and remote access
Records the temperature over the last 24 hours	Calcification protection
Display measured temperature and configure target temperature in the FRITZ!Fon, FRITZ!Box user interface or FRITZ!App Smart Home	Antifreeze function
Push service informs about loss of radio connection or low battery	Secure integration into home network via DECT ULE
	New features thanks to automatic updates

## Device properties

Dimensions (W x H x D): 93 x 51 x 51 mm	Radio range: up to 40 meters indoors
Weight: 150 g	Operational at an ambient temperature of 0°C to 50°C
Batteries: 3 x AA/Mignon/LR6	
Wireless standard: DECT ULE	

## **Installation and adapter**

Fits all common radiator systems (standard valve M30x1.5mm - Heimeier, Junkers, MNG, Braukmann, Oventrop, Honeywell, Landis+Gyr).

Adapter for Danfoss RA radiator valve included in delivery

You can find more information on installing on rare or very old radiators in the Knowledge Base

## **Package contents**

FRITZ!DECT 302

Adapter for Danfoss RA radiator valve

3 x AA batteries (in device)

Quick guide

## **System Requirements**

FRITZ!Box with DECT (except FRITZ!Box 7312/7412)

FRITZ!OS 6.83 and later

## **Article number**

20002961