



## USB Type C to Dual Display Converter, MST Hub

No.: 43280

Connect an HDMI and a VGA display simultaneously

### Description

- Connects an HDMI and/or VGA display to a USB Type C device
- Requires DisplayPort Alternate support from the USB Port/Bus
- Supports resolutions up to 3840x2160@30Hz 8bit RGB (HDMI) / 1920x1080@60Hz (VGA)
- Plug and Play, no drivers required
- 2 year warranty

USB Type C to Multi-AV converters allow users to connect multiple AV interfaces to a USB C equipped device. The Lindy USB Type C to Dual Display Converter allows users to connect two high definition displays using HDMI & VGA interfaces to a Macbook, ultrabook or notebook with USB DisplayPort Alternate Mode.

The Converter can send the same display information to two screens with SST technology or use both screens as individual displays with separate display information using MST functionality, this is easily configured using the display settings of your computer.

Installation is simple as no drivers are required, while Type-C's reversible design has been developed to work regardless of which way the cable is inserted into the port.

### Technical details

#### Specifications

- AV Interface: USB Type C to HDMI & VGA
- Interface Standard: HDMI 1.4, VGA
- Supported Bandwidth: 10.2Gbps
- Maximum Input Resolution: 3840x2160@30Hz 8bit RGB (HDMI) / 1920x1080@60Hz (VGA)
- Maximum Output Resolution: 3840x2160@30Hz 8bit RGB (HDMI) / 1920x1080@60Hz (VGA)
- Chipset: VL100,STDP4320,SN75DP149, PTN3355
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
- Power Delivery: -
- HDCP Support: HDCP 1.4
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: DisplayPort Alternate Mode, SST & MST support

#### Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x HDMI (Female), 1 x VGA (Female)

- Power: Bus-powered

#### **Physical Properties**

- Dimensions (approx.) WxDxH: 53.9x66.4x15.4mm [2.12x2.61x0.61in]
- (Fixed) Cable Length: 110mm [4.33in]
- Housing Material: Aluminum shell
- Net Weight: 0.08kg [0.18lb]
- Operating Temperature: 0°C - 45°C [32°F - 113°F]
- Storage Temperature: -10°C - 70°C [-4°F - 158°F]
- Humidity: 5% - 90% RH [ non-condensing]
- Power Requirements: -
- Colour: Grey

#### **Miscellaneous**

- Packaging Type: Polybag
- Packaging Dimensions: 176x194x20mm [6.93x7.64x0.79in]
- Gross Weight: 0.1kg [0.22lb]
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH, CP65

#### **Package Contents**

- USB Type C to Dual Display Converter

#### **Purchasing information**

- No.: 43280
- EAN: 4002888432801