

PREMIUM MATTE LABEL

Premium matte coated inkjet labels for high-quality photo-level printing with pigmented inks. The smooth, bright white surface with a matte finish, in combination with Epson DURABrite Ultra pigment inks, ensures fast drying, scratch, water and heat resistance. The universal permanent acrylic adhesive enables trouble free performance and good adhesion on variety of surfaces, also on low temperatures.

Suggested applications

- Barcode labels
- Box labels for consumer products
- Parts assembly labels
- Shelf-edge labels in Retail
- Pharmaceutical labels
- Sample labels in Healthcare
- Shipping labels

MATERIAL	
Facestock	88g/m ² (113μm) premium coated inkjet paper with matte finish
Adhesive	Acrylic based, permanent adhesive
Liner	51g/m ² (54μm) white kraft paper
Total calliper	186μm
TEMPERATURE RANGE	
Printing temperature	10 to 35°C
Printing humidity	20 to 80% RH (No condensation)
Minimum application temperature	5°C
Service temperature	-20 to 80°C
Storage (in original package)	up to one year in dry and dark conditions at a constant temperature (20°C, RH 50%)
SUPPORTED PRINTERS	
	Epson TM-C3400 Series
	Epson TM-C3500 Series
RECOMMENDED DRIVER SETTINGS	
TM-C3400	Media Type: Fine Media Label
	Media Layout: Full-page Label / Die-cut Label
	Print Quality: Speed / Quality
TM-C3500	Media Type: Matte Label
	Media Layout: Full-page Label / Die-cut Label
	Print Quality: Speed / Quality

Since all dyes, pigments and paper change over time, Epson does not warrant this product against colour changes and fading. Epson's liability for any defects in manufacturing and packaging is limited to the replacement cost of this product.

Best printing results achieved in a standard climate of 23°C and 50% relative humidity.

AVAILABLE SKUS

Type	SKU	EAN	Width (mm)	Length (mm)	Number of labels per roll	Number of rolls per box
 Roll, Continuous Label	C33S045417	8715946527048	51	35,000	1	24
	C33S045418	8715946527055	76	35,000	1	18
	C33S045419	8715946527062	102	35,000	1	18
 Roll, Die-cut Label	C33S045531	8715946537184	102	51	650	18
	C33S045532	8715946537191	102	76	440	18
	C33S045533	8715946537207	102	152	225	18
	C33S045534	8715946537214	76	51	650	18
	C33S045535	8715946537221	76	127	265	18