

FO outlet UP, 2 SC-S adapter OM3



Description

Fiber Optical flush-mounted data outlet to accommodate 2 SC-Simplex adapter or 2 LC-Duplex adapter. The data outlet is equipped with couplings in the classes OM3, OM4 or OS2 including shutter. **The highlight of this flush-mounted data outlet is that it not only has an integrated receptacle for excess fiber lengths, but also has a receptacle for splice protection (4x crimp or 4x shrink).** Depending on the application, the holder can also be dismantled so that it does not get in the way when pre-assembled cables are installed.

Performance features:

- Horizontal and vertical installation in the cable duct or flush mounting
- Recording of fiber overlengths
- Integrated splice protection for 4 splices
- Cover 80mm x 80mm
- Data outlet depth of 40mm for installation in flush-mounted boxes or cavity wall boxes

General data

Surface mounted	No
Flush mounted (plaster)	yes
Duct installation	yes
Type of fastening	Screw
With bus/coupling	yes
Number of buses/couplings	2
Equipped with adapters	SC simplex
Colour of adapter	aqua
Category	Multimode

This datasheet was created automatically on 04-05-2020 . Technical changes reserved.

FO outlet UP, 2 SC-S adapter OM3

General data

Max. Assembly (Adapter)	2
Suitable for adapter	SC Simplex/LC Duplex
With label space	yes
Centre plate	yes
Central plate according to	DIN 49075
Cover frame	yes
Cable strain relief	yes
Wire stock	yes
Outlet direction	down
Dust protection cap	shutter
Material bearing ring	Zinc alloy
Material central plate	ABS plastic
Material adapter plates	ABS plastic

Mechanical characteristics

Splice holder	crimp/ shrink
---------------	---------------

Dimensions






Dimension	80 x 80 x 40 mm
-----------	-----------------

Available variants

Article no.	Title	Colour	RAL-number	Dimensions
FTTH-OUTLET-SC-OM3	FO data outlet UP, 2 SC-S adapter OM3 with shutter, integrated splice holder	white	9010	80 x 80 x 40 mm

FO outlet UP, 2 SC-S adapter OM3

Technical drawings



This datasheet was created automatically on 04-05-2020 . Technical changes reserved.