

Product data sheet

Specifications



APC SurgeArrest Home/Office Surge Protector, 1x CEE 7/3 Schuko Outlet, 918 Joules, 2x USB Type-A Ports

PM1WU2-GR

Overview

Lead time

Main

Main Input Voltage	230 V
Input Connection Type	Schuko CEE 7/7P
Provided equipment	User manual

Physical

Colour	White
Height	10 cm
Width	6.3 cm
Depth	4.15 cm
Net weight	0.15 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50 Hz +/- 5 Hz
Maximum input current	16 A
Switching current capacity	16 A

Output

Number of power socket outlets	1
Outlet standard	Schuko CEE 7

Conformance

Product certifications	CE
Equipment protection policy	Lifetime : 50000 euros

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-5...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...4572.00 m

Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	30 dB
Peak current	24 kAcommon mode 12 kAnormal mode
Surge energy rate	918 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.8 cm
Package 1 Width	10.6 cm
Package 1 Length	7 cm
Package 1 Weight	0.23 kg
SCC14	10731304334757

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Limited Lifetime (European Union countries only)
----------	--------------------------------------------------

Recommended replacement(s)