LQ-2090IIN

DATASHEET / BROCHURE





Fast, networked 24-pin, 136-column dot matrix printer that offers outstanding reliability and an extremely low TCO.

The LQ-2090IIN is a high-volume dot matrix printer designed for fast and reliable printing. Upgrade your existing dot matrix printers to our latest model, which is now Energy Star compliant, and delivers built-in network capability with an incredibly low TCO.

Fast print speed

The LQ-2090IIN offers an improved USD (ultra speed draft) speed of 550 characters per second at 10 characters per inch, making a real difference to high-volume print runs such as stock reports and large batches of invoices or freight documents.

Increased reliability

Epson's dot matrix technology is already mature and very reliable. Building on this, the new printer improves the mean time between failure by 25% to 25,000 power-on hours, ideal for challenging conditions or where regular maintenance is not practical.

Same consumables

This printer uses the same ribbons as existing models, so you can upgrade your hardware and continue to use your current ribbon supplies.

Network capability

This is a network model which supports both serial and Ethernet connections for enhanced connectivity.

KEY FEATURES

- Fast print speed
 USD speed of 550 characters per second at 10 characters per inch
- Increased reliability
 Mean time between failure of 25,000
 power-on hours
- Increased number of copies Now original plus six copies
- Network capability
 Supports both serial and Ethernet connections
- Same consumables
 Uses the same ribbons as existing models
- Legal Statement

Complies with The UK Product Security and Telecommunications Infrastructure (Product Security) requirements. Epson will provide security updates for 7 years from purchase



PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method Impact dot matrix
Number of Pins 24 pins
Number of columns 136 columns
Pins 24 Needles

PRINT

Printing Speed Ultra Speed-Draft: 10 cpi: 550 chars/s

Barcodes Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E

Carbon Copies 6 plus one original

CONNECTIVITY

Interfaces Hi-Speed USB - compatible with USB 2.0 specification, Parallel, Ethernet interface (100 Base-

TX / 10 Base-T)

PAPER / MEDIA HANDLING

Document Feed Single sheet front and rear, Continuous media front and rear, Paper output rear

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels

(single- and multi-layer), Envelopes, Cardboard

Paper Thickness Continuous 0.12 mm - 0.46 mm

Pape

Paper Thickness Label Base 0.16 mm - 0.19 mm

Sheet

Paper Thickness Multi Part 0.12 mm - 0.46 mm Paper Thickness Single Sheet 0.065 mm - 0.14 mm

GENERAL

Power consumption 49 Watt

Product dimensions 612 x 375 x 177 mm (Width x Depth x Height)

Product weight 9.4 kg

Supported Temperature Operation 5° C - 35° C Supported Humidity Operation 10% - 80%

Compatible Operating Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8.1, Windows 8.1 x64 Edition,

Systems Windows Server 2003 x64, Windows Server 2016, Windows Vista, Windows Vista x64,

Windows XP, XP Professional x64 Edition

Mean Time Between Failures 25,000 hours

Print Head Life 400 Million Strokes/Wire Noise Operation:55 dB (A)
Noise Level Operation (Roll):55 dB (A)

OTHER FEATURES

Input Data Buffer 128 kB

OTHER

Warranty 12 months Carry in

Optional warranty extension available

LQ-2090IIN

WHAT'S IN THE BOX

- User manual
- Driver and utilities
- Ribbon
- Power cable



SUPPLIES

• Epson SIDM Black Ribbon Cartridge for LQ-2090 (C13S015336)


C13S015336

OPTIONAL ACCESSORIES

 Wide Pull Tractor Unit FX-2190II/LQ-2090II C12C933791

LOGISTICS INFORMATION

sku	C11CF40402A1
EAN code	8715946651392
Country of Origin	Indonesia
Layer	2 Units
Layer Block	3 Units



Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at https://www.epson.co.uk/contactus
* 10p per minute plus network extras.



Web: www.epson.co.uk www.epson.ie