Brodit
DEVICE MOUNTING SOLUTIONS



Active holder with cig-plug

Fits for devices with original skin. With tilt swivel and USB Host Type-A. With Easy-switching system. Charger via pogo pins. With AMPS, VESA 75 holes.

Item no: 712387
EAN Number: 7320287123876

Use an active holder for your Galaxy Tab Active while driving and you will always have a freshly charged battery! The holder provides a neat and comfortable installation - safe and convenient. The holder is equipped with a cig-plug for connection to the vehicle's 12/24 Volt socket. 3A charging. Charging via pogo plug. The holder is equipped with a USB-Host port so you can connect an accessory.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden.

Easy-switching system:
The easy-switching system enables you to upgrade the holder only, and keep the installed cables. It saves you a lot of time! When upgrading to a new device, you do not longer need to make a full installation. Same goes for maintenance in case of warranty or damage. You simply disconnect the holder from the charging cable via the Molex 6-pin quick connector, and then connect the new holder. The switch is done in a few seconds.

An installation of a tablet onto a vehicle’s dashboard is always done on the customer’s own responsibility. Brodit recommends to use tablets on the car’s headrest, installed onto a Brodit headrest mount.

Fits the following models:
Samsung Galaxy Tab Active 3 SM-T570/SM-T575
Samsung Galaxy Tab Active 5 SM-X300/SM-X306B

For a complete list, see
www.brodit.com/en/product/712387

Measurements:
Height 170 mm
Width 248 mm
Depth 45 mm
Volume 1897 cm³
Weight 383 g

Charging specifications:
Input voltage: DC/10-24V
Charging voltage: DC/4.6-5.3V
Output current(Typ): 3.0A
Input & output protection: Input polarity reversal/Output over voltage/Output over current/Output short protection
LED charging indicator: Product output indicator
Operating temperature: 0°C ~ +40°C
Storage temperature: -20°C ~ +80°C
RoHS compliant: ROHS