

USB-C to VGA and HDMI Adapter - 2-in-1 - 4K 30Hz - Space Grey

Product ID: CDP2HDVGA



Two-in-One Video Connectivity with Travel in Mind

Avoid the hassle of carrying different adapters, with a 2-in-1 USB-C monitor adapter. With VGA, and HDMI outputs, you can conveniently connect your laptop to any HDMI or VGA-equipped display, using this multiport adapter.

The adapter features a durable aluminum enclosure and can withstand being carried in your travel bag.

Ultra HD 4K 30Hz Resolution

The HDMI output on this USB-C video adapter supports UHD resolutions up to 4K 30Hz, while the VGA output supports HD resolutions up to 1920 x 1200.





Stylish Connectivity for Your MacBook, MacBook Pro, or Any Laptop

The USB-C video adapter has a Space Gray housing and built-in USB-C cable designed to match your Space Gray MacBook or MacBook Pro. The adapter is compatible with USB-C DP Alt Mode devices.

CDP2HDVGA is backed by a StarTech.com 3-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Connect to virtually any VGA or HDMI display while traveling
- Use as a video splitter to output an identical image to a VGA and HDMI monitor simultaneously splitting the image
- Output video to a secondary VGA, or HDMI monitor

Features

- Maximize your laptop's video compatibility with a 2-in-1 adapter: USB-C to HDMI® and VGA
- Support resource-demanding applications with UHD resolutions up to 4K 30Hz
- Space Gray adapter matches your Space Gray MacBook or MacBook
 Pro



Data Sheet

	Warranty	3 Years
Hardware	Active or Passive Adapter	Active
	Adapter Style	Adapters
	AV Input	USB-C
	AV Output	HDMI - 1.4
		VGA
	Chipset ID	ITE - IT6222
Performance	Audio Specifications	HDMI - 7.1 Channel Audio
	Maximum Analog Resolutions	1920 x 1200 @ 60Hz (VGA)
	Maximum Cable Distance To Display	15.2 m [49.9 ft]
	Maximum Digital Resolutions	3840 x 2160 @ 30Hz (HDMI)
	MTBF	1,576,016 hours
	Supported Resolutions	Maximum HDMI output:3840 x 2160 @ 30Hz
		Maximum VGA output: 1920 x 1200 @ 60Hz
		Lower resolutions and refresh rates may also be supported
	Video Revision	Lower resolutions and refresh rates may also be supported HDMI 2.0
Connector(s)	Video Revision Connector A	
Connector(s)		HDMI 2.0
Connector(s)	Connector A	HDMI 2.0 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
Connector(s) Special Notes / Requirements	Connector A	HDMI 2.0 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Female Output
Special Notes /	Connector A Connector B	HDMI 2.0 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - HDMI (19 pin) Female Output HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image
Special Notes /	Connector A Connector B	HDMI 2.0 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - HDMI (19 pin) Female Output HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image at a maximum resolution of 1920x1200 @ 60Hz Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of
Special Notes / Requirements	Connector A Connector B Note	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - HDMI (19 pin) Female Output HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image at a maximum resolution of 1920x1200 @ 60Hz Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling
Special Notes / Requirements	Connector A Connector B Note Humidity	HDMI 2.0 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - HDMI (19 pin) Female Output HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image at a maximum resolution of 1920x1200 @ 60Hz Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling 5~90% RH
Special Notes / Requirements	Connector A Connector B Note Humidity Operating Temperature	HDMI 2.0 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - HDMI (19 pin) Female Output HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image at a maximum resolution of 1920x1200 @ 60Hz Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling 5~90% RH 0°C to 45°C (32°F to 113°F)
Special Notes / Requirements Environmental	Connector A Connector B Note Humidity Operating Temperature Storage Temperature	HDMI 2.0 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input 1 - VGA (15 pin, High Density D-Sub) Female Output 1 - HDMI (19 pin) Female Output HDMI and VGA can output video at the same time. If both video outputs are connected, they'll display the same image at a maximum resolution of 1920x1200 @ 60Hz Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling 5~90% RH 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F)



Data Sheet

	Material	Aluminum
	Product Height	1.5 cm [0.6 in]
	Product Length	205 mm [8.1 in]
	Product Width	62 mm [2.4 in]
	Weight of Product	43 g [1.5 oz]
Packaging Information	Package Height	20 mm [0.8 in]
	Package Length	17.9 cm [7 in]
	Package Width	8 cm [3.1 in]
	Shipping (Package) Weight	0.1 kg [0.1 lb]
What's in the Box	Included in Package	1 - Travel A/V Adapter

Product appearance and specifications are subject to change without notice.