

Industrial Gigabit PoE Injector - High Speed/High Power 90W - 802.3bt PoE++ 48V-56VDC DIN Rail
UPoE/Ultra Power Over Ethernet Injector Adapter -40C to +75C Rugged

Product ID: POEINJ1G90W



This Gigabit Power over Ethernet (PoE+) injector supplies power and data connectivity to a Gigabit PoE-compliant device using a standard Ethernet cable.

Compatible with IEEE 802.3bt and most previous 90W proprietary PoE (Ethernet) standards, including PoH (HDBaseT), Cisco uPoE, Bosch, and AXIS. One product can cover multiple use requirements to improve standardization and deployment and dual power terminal block inputs provide redundancy for critical applications.

As many typical PoE-enabled switches max out at 30W a high 90W power budget is perfect for demanding Type 3 and Type 4 PoE applications like tilt and pan cameras and high power IEEE 802.11ax wireless access points.

Industrial features include -40 C to 75 C operating temperature, IP-30 rated housing, vibration, shock, and free-fall standard testing.

- Vibration: EN 60068-2-6
- Shock: EN 60068-2-27
- Free-fall: EN 60068-2-32

500,000+ hours MTBF rating using Telcordia/Bellcore at 50C for long-term reliability.

The POEINJ1G90W is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

Features

- **WIDE STANDARD COMPATIBILITY:** High speed Industrial Gigabit PoE Injector compatible w/ IEEE 802.3bt (PoE++) & previous 90W proprietary POE standards including PoH (HDBase-T), Cisco uPoE, Bosch & AXIS
- **90W POWER BUDGET:** Provides up to 90W of auto-negotiated power output for Type 3 and Type 4 PoE/Ultra/UPoE applications like tilt and pan cameras and high power IEEE 802.11ax wireless access points
- **TECH SPECS:** 1 Gbps 48V-56VDC Power Input IEEE 802.3af IEEE 802.3at IEEE 802.3bt 90W max PoH (HDBase-T) uPoE 10/100/1000 Mbps Auto Negotiation DIN/Wall Mountable Redundant Power Input
- **ROBUST DESIGN:** Industrial Power over Ethernet Injector w/MTBF of 500,000+hrs @ 50C Vibration, shock & free fall rated Rugged IP-30 aluminum housing Hardened operating temp of -40C to 75C
- **STARTECH.COM ADVANTAGE:** IT professionals' choice for over 30 years This PoE Injector is backed for 2-years by StarTech.com, including free 24/5 North America based multi-lingual tech support

Hardware

Warranty	2 Years
Ports	2
Industry Standards	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3at PoE Plus, IEEE 802.3af Power over Ethernet, IEEE 802.3bt
Chipset ID	Microsemi PD69204

Performance

Maximum Cable Length	328.0 ft [100 m]
Surge Protection	2kV,
Compatible Networks	10/100/1000 Mbps
Auto MDIX	Yes
Full Duplex Support	Yes
Jumbo Frame Support	9K max.
General Specifications	ESD Standard: IEC 61000-4-2: Contact: 6KV; Air: 8KV, EFT Standard: IEC 61000-4-4: Power: 2KV; Signal: 2KV, Surge Standard: IEC 61000-4-5: Power: 2KV; Signal: 2KV, Vibration Standard: EN 60068-2-6, Shock Standard: EN 60068-2-27, Free-Fall Standard: EN 60068-2-32, Housing Standard: IP-30, Safety Standard: EN60950-1
MTBF	540,891 hours

Supported Protocols		CSMA/CD, IEEE 802.3at, IEEE 802.3af, IEEE 802.3bt,
Connector(s)		
Connector Type(s)		Ethernet Gigabit
		RJ-45 (PoE+)
		Terminal Block (4 Wire)
Special Notes / Requirements		
Patents and Licenses		United States Patent No. 5,406,260 (expired) , United States Patent No. 6,650,622, United States Patent No. 7,457,250, United States Patent No. 8,155,012, United States Patent No. 8,902,760, United States Patent No. 8,942,107, United States Patent No. 9,019,838, United States Patent No. 9,049,019, United States Patent Application No. 14/695,456, United States Patent Application No. 14/726,940,
Indicators		
LED Indicators		Power
		PoE
Power		
Plug Type		N
Environmental		
Operating Temperature		-40°C to 75°C
Storage Temperature		-40°C to 85°C
Humidity		5 to 95% (non-condensing)
Physical Characteristics		
Color		Black
Material		Aluminum
Cable Length		328.0 ft [100 m]
Product Length		3.2 in [81.5 mm]
Product Width		1.3 in [32.0 mm]
Product Height		4.1 in [10.4 cm]
Weight of Product		6.1 oz [174.0 g]

**Packaging
Information**

Package Length	6.4 in [16.2 cm]
Package Width	8.3 in [21.1 cm]
Package Height	2.5 in [64.0 mm]
Shipping (Package) Weight	14.7 oz [416.0 g]

**What's in the
Box**

Included in Package	Industrial-Grade PoE Injector
	Mounting Hardware Kit
	Quick-Start Guide
	Terminal Block

****Product appearance and specifications are subject to change without notice.***

